

# KR Series

## Card Readers



KR100-E/M



KR101-E/M




KR102-E/M



KR503-E/M



KR500-E/M



KR501-E/M



KR502-E/M

## RFID/Mifare Card Readers

### Part Numbers

KRxxx-E: 125 KHz Proximity Card Reader

KRxxx-M: 13.56 MHz Mifare Card Reader

### Reading Time

<300ms

### Input Port

External LED Control  
External Buzzer Control

### Output Format

E-Models  
26bit Wiegand  
1's/5's M-Models  
Default: 26 bit format  
(Optional 34 bit format available)

### Power/Current

6-14V DC/70mA

### LED

Red and Green LEDs

### Beeper

Yes

### Operating Temperature

14F° to 158F° (-10° to +70°C)

### Operating Humidity

10% to 90% relative humidity non-condensing

### Index of Protection

Waterproof IP65  
Reverse Polarity Protection

## Dimensions

	KR100 E/M	KR101 E/M	KR102 E/M	KR500 E/M	KR501 E/M	KR502 E/M	KR503 E/M
<b>Height:</b>	4.57in (11.6cm)	3.05in (7.75cm)	3.39in (8.6cm)	4.57in (11.6cm)	3.39in (8.6cm)	3.39in (8.6cm)	4.57in (11.6cm)
<b>Length:</b>	2.95in (7.5cm)	1.69in (4.28cm)	3.39in (8.6cm)	2.95in (7.5cm)	3.39in (8.6cm)	3.39in (8.6cm)	2.95in (7.5cm)
<b>Width:</b>	0.69in (1.75cm)	0.65in (1.65cm)	0.65in (1.63cm)	0.68in (1.73cm)	0.63in (1.6cm)	0.79in (2.0cm)	0.68in (1.73cm)
<b>Weight:</b>	0.35lbs (0.16kg)	0.15lbs (0.07kg)	0.30lbs (0.14kg)	0.15lbs (0.07kg)	0.30lbs (0.14kg)	0.30lbs (0.14kg)	0.35lbs (0.16kg)



Design and Specifications subject to change without notice

### ZKAccess

201 Circle Drive North, Suite 116  
Piscataway, NJ 08854, USA  
Tel: +1 732-412-6007  
Fax +1 732-412-6008

sales@zkaccess.com  
zkaccess.com

