



Security Locks

Press and Swing Handel Lock



Side Panel


Easy to Remove by Slide Lock and Security Lock



Double Part



Single Part



Mounting Pole

Rack Unit (U) Screen on Pole



Grounding Kit

Connecting Between Frame and Front Door

LINK Glass Wall Rack Features

- Suitable for indoor installation (Wall mount type) which consist of front door, center panel and back base. Center panel equipped with rollers for opening and locking to back base part (excluding for 40cm depth).
- Rack was made from Electro Galvanized Sheet 1.0mm thickness, also have 4-Mounting pole 2.0mm thickness.
- Front door "See-through" Tempered Glass 5.0mm thickness (for LINK Glass Wall Rack) and perforated surrounding for ventilation, also have swing handle locked.
- Steel frame are dismountable and can fasten the wall with screws.
- Mounting pole can be adjustable in/out with Rack Unit (U) screen on pole.
- Cable entry at the top and the base.
- Raised roof with vented and perforated surrounding for ventilation, also can be mounted the fan sets (3 fans maximum installation).
- Set of nut and screw according to the size of Rack, and 4 sets of wall mounting screw.
- Both side panels are easy to open by slide locked, also have security locked for installation and maintenance.
- 180° opening door, and can change the opening direction.
- Grounding kit which connect between frame and front door.
- Wide range of supplementary accessories : shelves, drawers, fan sets, power distribution unit.

Standards

- 19" Standard, ISO9001:2008 (New version 2015) and ISO14001
- ANSI/EIA-310D, IEC297-1, IEC297-2, BS5954 Part : 2, DIN 41494

Specifications

Material

- Frame : 1.2 mm thick sheet steel
- Rear and Side Panels : 1.0 mm thick sheet steel
- Solid blanking plate : 1.0 mm thick sheet steel
- Glass Door : 5.0 mm thick safety glass
- Mounting Pole : 2.0 mm galvanized steel with Zinc coated

Surface Finishing

- Electrostatic powder coating, Black (RAL9004)

Scope of Delivery

- Cabinets are packed in cartons.

Ordering information

U Height (U=4.45 cm.)	Width (cm.)	Depth		Height (cm.)	Order Number
		(cm.)	(Part)		
6U	60	40	Single	37	CW1-60406G
	60	50	Double	37	CW2-60506G
	60	60	Double	37	CW2-60606G
9U	60	40	Single	50.5	CW1-60409G
	60	50	Double	50.5	CW2-60509G
	60	60	Double	50.5	CW2-60609G
12U	60	40	Single	64	CW1-60412G
	60	50	Double	64	CW2-60512G
	60	60	Double	64	CW2-60612G