


WALL RACK OUTDOOR

G1 SERIES



19"GERMANY[®]
EXPORT RACK



Push Handle Lock



Rubber Seal




Mounting Pole
w/Screen UH



Mounting Pole
Can be Adjusted



3 Knock Out Holes



Grounding



FEATURES

- ◆ **Designed** to comply with the standard of ANSI/EIA-310D-1992 (Rev.EIA-310C).
- ◆ **19"Wall Rack type** for outdoor, suitable for Network Equipment 19" standard or FDU, Patch Panel and suitable for CCTV system.
- ◆ **Designed with a height** of 6U, 9U or 12U.
- ◆ **The cabinet compliant** with IP54 (Dust and Water protection).
- ◆ **Designed of two layer**, The front and side panel have a sun shield layer for outdoor Harsh Environment installation.
- ◆ **Structure** Produced from Electro-Galvanized Sheet steel with thickness of 1.2 mm., Light weight and completed rust proof.
- ◆ **Front door** Designed of two layers, provide build in Push Handle Lock. Ventilation by roofer at front door. Open through 180 degrees.
- ◆ **Side Panel (two doors)** Designed of two layers with two security lock for safety. Water proof, dust filter and ventilation by roofer at side panel. Open through 120 degrees.
- ◆ **Back Side** Supporting by four steel support bar with thickness of 2.0mm.
- ◆ **Roof cover** The top can be mounted with 1 to 3 of 4" ventilating fans to release the accumulated heat inside the cabinet and extend the life of equipment., On the roof cover has the ventilation grill.
- ◆ **Front door, Side panel and Roof cover** are water proof by special rubber seal.
- ◆ **Mounting pole** Produced from Electro-Galvanized steel with thickness of 2.0 mm. They can be adjusted in/out (8 level) to meet customer's need. Provide the U-height screened on the mounting pole.
- ◆ **Base** Provide removable plate with rubber shield., Provide 3 knock out holes size 3/4" and 1" for cable entry.
- ◆ **Grounding** Provide 3 ground wires connecting between structure and doors.
- ◆ **Color** The Special dark gray for outdoor color by electrostatic powder coating paint., Scratch resistance and rust protection.
- ◆ **Manufacturing and Distribution** Compliant with ISO 9001:2008

ORDERING INFORMATION

Order No.	Description	Color
G1-60406OUT	19"GERMAN WALL RACK OUTDOOR, 6U, D 40 cm.	Dark Grey
G1-60409OUT	19"GERMAN WALL RACK OUTDOOR, 9U, D 40 cm.	Dark Grey
G1-60412OUT	19"GERMAN WALL RACK OUTDOOR, 12U, D 40 cm.	Dark Grey
G1-60506OUT	19"GERMAN WALL RACK OUTDOOR, 6U, D 50 cm.	Dark Grey
G1-60509OUT	19"GERMAN WALL RACK OUTDOOR, 9U, D 50 cm.	Dark Grey
G1-60512OUT	19"GERMAN WALL RACK OUTDOOR, 12U, D 50 cm.	Dark Grey
G1-60606OUT	19"GERMAN WALL RACK OUTDOOR, 6U, D 60 cm.	Dark Grey
G1-60609OUT	19"GERMAN WALL RACK OUTDOOR, 9U, D 60 cm.	Dark Grey
G1-60612OUT	19"GERMAN WALL RACK OUTDOOR, 12U, D 60 cm.	Dark Grey

Recommend Accessories

Order No.	Description	Color
G7-05001	1 x Ø 4" Heavy Duty Fan	Black
G7-05002	2 x Ø 4" Heavy Duty Fan	Black, Light Grey
G7-00006	AC Power Distribution 6 Outlet w/Cable 3M & Surge Protection	Light Grey