VENTILATING FAN

















Plastic Guard







Frame

FEATURES

- Designed For heat ventilation in the cabinet.
- Manufactured Designed with 2 Ball bearing Heavy duty. Impellers made from fiberglass reinforced plastic which comply to UL94V-0 and impedance protection.
- Dimension 120x120x38mm with Die-Cast Aluminum Housing and 7.0mm thickness, Black ABS plastic guard with 19" Germany Export Rack trademark.
- Frame Made from Electro-Galvanized Steel sheet in light gray color painted by Electrostatic powder coating process.
- Power Cord

1.80m, 2x0.5mm² (≈20AWG) for 1xø4" Fan. 1.40m, 3x0.82mm² (≈18AWG) for 2xø4", 3xø4" Fan.

Assembly and Distributor By ISO 9001 : 2015 Company.

Technical Specification

- Speed : 2,650 rpm @ 50 Hz , 3,000 rpm @ 60 Hz

- Max. Air-Flow : 2.38 m³/min or 84.8 CFM

- Max. Input Power : 22 Watts @ 50 Hz , 19 Watts @ 60 Hz

- Acoustical Noise : 46 dB (A)

Input Voltage : 220-230 VAC , 50/60 Hz
Operating Temperature : -30°C to +70°C

- Life Expectancy : 50,000 Hours Continuous

- Approval : CE & UL/CSA

Options

- Color : *Black color (as requested)

ORDERING INFORMATION

1	Order No.	Description	Figure
	G7-05001	1 x Ø 4" HEAVY DUTY FAN (Individual) w/Cable 1.8 M	Α
	G7-05002	2 x Ø 4" HEAVY DUTY FAN SET w/Cable 1.4 M	В
	G7-05003	3 x Ø 4" HEAVY DUTY FAN SET w/Cable 1.4 M	С

* Order No. for Black Color : G7-050XXB

Sample: G7-05002B 2 x Ø 4" HEAVY DUTY FAN SET w/Cable 1.4 M., Black Color