

MONITOR
G32C4X
G32C4X

## PATH TO THE FUTURE

Inspired by the rigorous quality testing in the production of MSI G series, MSI G series' design is full of symbols of sturdiness and durability. Additionally, to provide quality user experience, G series has really simple installation process and a friendly user interface, and will be the best choice for entry level gamers to step into the game world.



Picture and logos

## **SELLING POINTS**

- Curved Gaming display (1500R) The best gameplay immersion.
- 250Hz Refresh Rate Real smooth gaming.
- 1ms response time eliminate screen tearing and choppy frame rates.
- Wide Color Gamut Game colors and details will look more realistic and refined, to push game immersion to its limits.
- AMD FreeSync™ Premium Technology Tear free, stutter free, fluid gaming.
- Anti-Flicker and Less Blue Light game even longer and prevent eye strain and fatique.
- Frameless design Ultimate gameplay experience.
- 178° wide view angle.



- 1. 5-way joystick navigator
- 2. 1 x DC Jack
- 3. 1 x Display Port 1.2a
- **4.** 2 x HDMI<sup>™</sup> 2.0
- 5. 1 x Earphone out
- **6.** 1 x Kensington lock



M O N I T O R G32C4X

## **SPECIFICATION**

EAN UPC UCC14 Part No MKT Name MKT Spec	4711377084550 824142319338 10824142319335 9S6-3DA61T-044 G32C4X
UCC14 Part No MKT Name	10824142319335 9S6-3DA61T-044
Part No MKT Name	9S6-3DA61T-044
MKT Name	
	D L 1/ D . T / D
	G32C4X
Color	ID1/Black-Black
Screen Size	31.5" (80 cm)
	698.4(H)x392.85(V)
	Curve 1500R
	VA
	1920x1080 (FHD)
	16:9
<u> </u>	FreeSync Premium
	HDR Ready
	300
-	3000:1
	100000000:1
	242~277 KHz(H) / 96~250 Hz(V)
	250Hz
	1ms(MPRT)
· ·	4ms
	178°(H)/178°(V)
•	Anti-glare
	100.07%/86.78%
	85.94%/80.71%
	114.77%/97.72%
	121.34%/99.39%
	98.35%/89.62%
	89.93%/83.53%
	91.4%/91.08%
· · · · · · · · · · · · · · · · · · ·	89.45%/89.28%
Rec.709 (CIE1976 area percentage/overlap)	114.77%/97.72%
Rec.709 (CIE1931 area percentage/overlap)	121.34%/99.39%
Rec.2020 (CIE1976 area percentage/overlap)	66.6%/66.6%
Rec.2020 (CIE1931 area percentage/overlap)	64.17%/64.17%
Display Colors	1.07B
Color bit	10 bits (8 bits + FRC)
Note_DP	1920 x 1080 (Up to 250Hz)
Note_HDMI™	1920 x 1080(Up to 240Hz)
Note_DVI	N/A
HDMI™	2
HDMI™ version	2.0b
HDMI™ HDCP version	2.3
DisplayPort	1
DisplayPort version	1.2a
DisplayPort HDCP version	2.3
Headphone-out	1
Lock type	Kensington Lock
Power Type	External Adaptor 20V 3.25A
Power Input	100~240V, 50/60Hz
Energy Efficiency Rating	F
Adapter's KC safety Number	SU10469-13001
Power Cord Type	C5
	Active Display Area (mm) Curvature Panel Type Resolution Aspect Ratio Dynamic Refresh Rate technology HDR (High dynamic range) SDR Brightness (nits) Contrast Ratio DCR (Dynamic Contrast Ratio) Signal Frequency Refresh Rate Response Time (MPRT) Response Time (GTG) View Angles Surface Treatment NTSC (CIE1976 area percentage/overlap) SRGB (CIE1931 area percentage/overlap) sRGB (CIE1931 area percentage/overlap) Adobe RGB (CIE1976 area percentage/overlap) DCI-P3 (CIE1931 area percentage/overlap) DCI-P3 (CIE1976 area percentage/overlap) Rec.709 (CIE1976 area percentage/overlap) Rec.709 (CIE1976 area percentage/overlap) Rec.2020 (CIE1931 area percentage/overlap) Rec.2020 (CIE1931 area percentage/overlap) Rec.2020 (CIE1976 area percentage/overlap) Rec.2020 (CIE1976 area percentage/overlap) Rec.2020 (CIE1976 area percentage/overlap) Rec.2020 (CIE1976 area percentage/overlap) Rec.2020 (CIE1931 area percentage/overlap) Display Colors Color bit Note_DP Note_HDMI™ Note_DVI HDMI™ HDMI™ HDMI™ HDMI™ HDCP version DisplayPort version DisplayPort version DisplayPort version DisplayPort version DisplayPort HDCP version Headphone-out Lock type Power Type Power Input Energy Efficiency Rating Adapter's KC safety Number



M O N I T O R
G32C4X

	3.5mm Mic Cable	0
In The Box	Switch Case	0
	Portable Screen Protection Case	0
	Monitor Hood	0
	Speaker (Accessories)	0
	DisplayPort Cable	1
	HDMI™ Cable	0
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	Mouse Bungee Unit	0
	VESA Screw	0
	Power Cord	1
	AC Adaptor	1
	Warranty Card	0
Design	Quick Guide	1
	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
-	Frameless Design	Yes
Outer Carton Dimension (WxDxH)	Outer Carton Dimension (WxDxH) (inch)	7.2 x 38.78 x 21.18
Product Dimension with Stand (WxDxH)	Product Dimension with Stand (WxDxH) (mm)	709.4 x 248.7 x 509.4
	Product Dimension with Stand (WxDxH) (inch)	27.93 x 9.79 x 20.06
Product Dimension without Stand (WxDxH)	Product Dimension without Stand (WxDxH) (mm)	709.4 x 92 x 429.3
	Product Dimension without Stand (WxDxH) (inch)	27.93 x 3.62 x 16.9
Stand Dimension (WxDxH)	Stand Dimension (WxDxH) (mm)	452.8 x 248.7 x 265.5
	Stand Dimension (WxDxH) (inch)	17.83 x 9.79 x 10.45
Dimension & Weight	Inside Carton Dimension (WxDxH) (inch)	6.61 x 38.19 x 20.2
	Weight (Net kg)	6.3
	Weight (Gross kg)	9.
Weight	Weight Without Stand (kg)	5.5
Warranty	Warranty	36M
-	The state of the s	I .