

PANTUM

The New Era for Printing

M6800/M7200 Series
Monochrome laser multifunction printer

Enjoy additional value with the 4in1 high speed printer

Get additional value from the Pantum 4in1 M6800 and M7200 series with print, copy, scan, and fax functions, high print and copy speed, auto-duplex printing, budget-saving separate drum unit and toner cartridge and class-leading memory. They can serve as ideal multifunction tools for rapidly growing and large business.



4 IN 1 Print/Copy/Scan/Fax



**Wifi One Step Installation
and Direct Printing**



**Office document direct
print from mobile devices**



**Automatic duplex
printing**



ADF Scan up to 24 ppm



Convenient to print



Separate drum and toner

PANTUM

WWW.PANTUM.COM

KEY SPECIFICATIONS



M6800 /M7200 Series
Monochrome laser multifunction printer

Model	M6800FDW	M7200FD	M7200FDN	M7200FDW
Printing				
Print speed	30ppm(A4) / 32ppm(Letter) †		33ppm(A4) / 35ppm(Letter)	
Resolution (print,copy,scan,fax) ⁽¹⁾	Print: 1200 x 1200 dpi(Max); Copy: 600 x 600 dpi(Max); Scan: Flatbed 1200x1200dpi(Max) / ADF 600x600dpi(Max)			
First print out time	Less than 7.8s †		Less than 8.2s	
Max. monthly volume	60000 pages			
Recommended monthly volume	750 to 3000 pages			
Processor speed	600 MHz			
Memory	256 MB			
Printer language	GDI †		PCL5e, PCL6, PS, PDF	
Copying				
Copy speed	30cpm(A4) / 32cpm(Letter) †		33cpm(A4) / 35cpm(Letter)	
First copy out time	FB: Less than 10s; ADF: Less than 11s			
Zoom	25% - 400%			
Max. copy pages	1 - 99 pages			
Additional function	ID copy, Receipt copy, N-up copy, Clone copy, Poster copy, Manual duplex copy, Collated copy			
Scanning				
Scan speed	24 ppm(A4) / 25 ppm(Letter)			
Max. scan size	Flatbed 216 x 297 mm / ADF 216 x 356mm			
Output function	Scan to E-mail, PC, FTP, Thumb drive, iOS/Android †	Scan to PC, Thumb drive †	Scan to E-mail, PC, FTP, Thumb drive †	Scan to E-mail, PC, FTP, Thumb drive, iOS/Android †
Color scanning	Yes			
Faxing				
Fax type	Mono			
Modem speed	33.6Kbps			
Memory	650 pages			
Coded system	MH / MR / MMR / JBIG			
Compatibility	ITU-T SG3 / ECM			
Fax feature	PC-FAX(only sending), Junk Fax Barrier, Multi-send, Fax Forwarding, Quick-dial, Group Dial, Delayed Send, Auto Redial, Auto Receive, Auto Reduction, Mobile Fax			
Paper handling				
Paper input tray	250 pages			
Multipurpose tray	1 page			
Paper output tray	150 pages (A4/70g)			
ADF Capacity	50 pages			
Media types	Plain, Thick, Thin, Transparency, Cardstock, Label, Envelope			
Media sizes	A4, A5, JIS B5, ISO B5, A6, Letter, Legal, Executive, Folio, Oficio, Statement, Japanese Postcard, Monarch Env, DL Env, C5 Env, C6 Env, No.10 Env, ZL, Big 16K, Big 32K, 16K, 32K, B6, Yougata4, Postcard, Younaga3, Nagagata3, Yougata2, Custom			
Media weight	Input tray: 60-105g/m ² Multipurpose tray: 60-200g/m ²			
General				
Dimensions (wxdxh)	415 x 365 x 350mm (16.3 x 14.4 x 13.8in)			
Weight (without toner cartridge)	11.39kg (25.1lb)			
Input voltage	110V Model: AC100-127V(±10%), 50/60Hz(±2Hz), 9A 220V Model: AC220-240V(-15%, +10%), 50/60Hz(±2Hz), 4.5A			
Noise	Printing: ≤52dB(A) Copying: ≤54dB(A) Scanning: ≤52dB(A) Standby: ≤30dB(A)			
Operating system compatibility	Windows Server2003 / 2008 / 2012 / XP / Vista / Win 7 / Win 8 / Win8.1 / Win10 (32/64 Bit); Mac OS 10.7-10.13; Linux: Ubuntu12.04/14.04 (32/64 Bit)			
Mobile Operating system compatibility	iOS 7.0 and above; Android 4.4 and above †		iOS 7.0 and above; Android 4.4 and above †	
Interface	Hi-Speed USB2.0 † Net: IEEE 802.3 † 10/100Base-Tx † WiFi: IEEE 802.11b/g/n †	Hi-Speed USB2.0 †	Hi-Speed USB2.0 † Net: IEEE 802.3 † 10/100Base-Tx †	Hi-Speed USB2.0 † Net: IEEE 802.3 † 10/100Base-Tx † WiFi: IEEE 802.11b/g/n †
Supplies				
Cartridge style	Separate drum and toner			
Starter cartridge capacity / Drum unit lifetime ⁽²⁾ <small>(Print with A4 paper page by page discontinuously)</small>	TL-410E (1000 pages) † / DL-410E (9000 pages) †		TL-410 (1500 pages) / DL-410 (12000 pages)	
Cartridge and drum capacity ⁽²⁾	Cartridge: TL-410 (1500 pages, Standard); TL-410H (3000 pages, High); TL-410X (6000 pages, Extra high) Drum: DL-410 (12000pages)			

(1) Up to

(2) As per ISO/IEC 19752 specification (Individual users will experience different results based on their environment and page coverage)

Copyright © 2017 Pantum International Limited. The information contained herein is subject to change without notice. Pantum shall not be liable for technical or editorial errors or omissions contained herein.