

## Modern MD241P

MODERN MD241P

## PATH TO THE FUTURE



### **Selling Points**

#### **Modern MD241P**

MSI Modern MD241P Series Monitor - 23.8-inch, Full HD, Less Blue Light, Anti-Flicker, Anti-Glare, Display Kit, VESA Mount Support & Built-in Speakers, Designed for pursuing a Elegant and personalized design fit in anywhere in your house.

- TÜV certification display protect your eyesight and keep your eyes healthy
- Less blue light and anti-flicker technology prevent your eyes from strain & fatigue
- 75 Hz refresh rate provides better viewing experience
- Work with a comfortable viewing position while focusing on your courses and homework
- Keep the flexibility for your different devices with dual sources, HDMI & Type-C ports
- The standard VESA-mount supported
- Always allows you to join online conference call with built-in speakers



Picture and logos: Pictures Business Productivity Monitor



- **1.** 1x HDMI(1.4b)
- 2. 1x D-Sub (VGA)
- 3. 1x Mic-in
- 4. 1x Headphone-out
- **5.** 1x Kensington Lock




# Modern MD241P

MODERN MD241P

# **Specification**

Specification	
USB 3.2 Gen 2x2 Type C	NA
USB 3.2 Gen 2x2 Type A	NA
USB 3.2 Gen 1 Type C	NA
USB 3.2 Gen 1 Type A	NA
USB 2.0 Type A	NA
USB 2.0 Type C	NA
Card Reader	NA NA
Inside Carton Dimension (WxDxH) (mm)	804 x 157 x 395
Inside Carton Dimension (WxDxH) (inch)	31.65 x 6.18 x 15.55
Weight (Net kg)	4.7
Weight (Gross kg)	6.5
Warranty	36M
AC Adaptor	1
Power Cord	1
Warranty Card	1
Quick Guide	1
Entity MKT Name	Modern MD241P
EAN	4719072785086
UPC	824142237434
UCC14	10824142237431
Thunderbolt	NA NA
Local Dimming	NA NA
Screen Size	23.8" (60cm)
Active Display Area (mm)	527.04(H)*296.46(V)mm
Curvature	Flat
Panel Type	IPS
Resolution	1920x1080 (FHD)
Pixel pitch	0.2745(H)X0.2745(V)
Aspect Ratio	16:9
Dynamic Refresh Rate technology	NA
Activated Range	NA NA
HDR (High dynamic range)	NA NA
SDR Brightness (nits)	250
Contrast Ratio	1000:1
DCR (Dynamic Contrast Ratio)	100000:1
Signal Frequency	30~112 KHz(H) / 48~75 Hz(V)
Refresh Rate	75Hz
Response Time (MPRT)	NA NA
Response Time (GTG)	5ms
Response Time (Tr + Tf)	14ms
View Angles	178°(H)/178°(V)
NTSC (CIE1976 area percentageoverlap)	95.98%/80.61%
NTSC (CIE1931 area percentageoverlap)	77.71%/73.10%
sRGB (CIE1976 area percentageoverlap)	110.03%/98.38%
sRGB (CIE1931 area percentageoverlap)	109.71%/98.07%
Adobe RGB (CIE1976 area percentageoverlap)	94.21%/85.65%
Adobe RGB (CIE1931 area percentageoverlap)	81.33%/75.91%
DCI-P3 (CIE1976 area percentageoverlap)	87.72%/85.19%
DCI-P3 (CIE1931 area percentageoverlap)	80.87%/80.33%
Rec.709 (CIE1976 area percentageoverlap)	NA
Rec.709 (CIE1931 area percentageoverlap)	NA
Surface Treatment	Anti-glare
Display Colors	16.7M
Color bit	8 bits
Note_DP	NA
Note_HDMI	1920 x 1080 (Up to 75Hz)
Note_DVI	N/A
HDMI	1
HDMI version	1.4
HDMI HDCP version	1.4
DisplayPort	NA NA
DisplayPort version	NA
DisplayPort HDCP version	NA
- p. //gr	





## Modern MD241P

MODERN MD241P

The state of the s	NA.
Thunderbolt version	NA
Thunderbolt HDCP version	NA .
USB Type C (DisplayPort Alternate)	1
DVI	NA
D-Sub	NA
Mic-in	NA
Mic-in upstream	NA .
Headphone-out	1
Audio Combo	NA
USB 2.0 Type B	NA
USB 3.2 Gen 1 Type B	NA
Lock type	Kensington Lock
Power Type	External Adaptor 19V 2.58A
Power Input	100~240V, 50/60Hz
Adapter's KC safety Number	NA COLOR OF THE CO
Power Cord Type	C13
QC Output	NA
QC Output Power	NA NA
PD Output	NA NA
PD Output Power	NA For 200
Adjustment (Tilt)	-5° ~ 20°
Adjustment (Swivel)	-30° ~ 30°
Adjustment (Height)	0 ~ 110 mm
Adjustment (Pivot)	-90° ~ 90°
VESA Mounting	75x75mm
Frameless Design	Yes
Outer Carton Dimension (WxDxH) (mm)	814 x 167 x 417
Outer Carton Dimension (WxDxH) (inch)	32.05 x 6.57 x 16.42
Product Dimension with Stand (WxDxH) (mm)	541 x 200 x 380
Product Dimension with Stand (WxDxH) (inch)	21.3 x 7.87 x 14.96
Product Dimension without Stand (WxDxH) (mm)	541 x 48 x 322
Product Dimension without Stand (WxDxH) (inch)	21.3 x 1.89 x 12.68
Stand Dimension (WxDxH) (mm)	230 x 200 x 415
Stand Dimension (WxDxH) (inch)	9.06 x 7.87 x 16.34
Weight (Net Ibs) Weight (Gross Ibs)	10.36 14.33
Feature	
Certification	Frameless design 全球(WW)/CB
Certification	EU(歐洲)/CE-LVD DE(德國)/FCC DOC TW(台灣)/BSMI AU(澳大利亞)/RCM/MEPS JP(日本)/PSE,VCCII CCC
DisplayPort Cable	0
HDMI Cable	1
DVI Cable	0
USB Type A to Type B Cable	0
USB Type C to Type A Cable	0
USB Type C to Type C Cable	0
Thunderbolt Cable	0
VGA Cable	0
3.5mm audio Cable	0
3.5mm combo audio Cable	0
HDR Brightness (Peak nits)	NA
Rec.2020 (CIE1976 area percentageoverlap)	N/A
Rec.2020 (CIE1931 area percentageoverlap)	N/A