


PATH TO THE FUTURE



Picture and logos

SELLING POINTS

- Perfect 27" screen size for the programming, coding & website design workspace
- TÜV certified display protects your eyesight and keeps your eyes healthy
- Anti-Flicker technology prevents your eyes from strain & fatigue
- Less Blue Light PRO technology simultaneously protects your eyes and keeps vivid color & detail.
- Ergonomic software, Display Kit, provides the most convenient tool, the proper color & display mode to you while working with it every day
- IPS grade panel brings a breathtaking screen clarity
- 100Hz refresh rate provides a better viewing experience
- Keep the flexibility for your different devices with multiple input sources: DisplayPort, HDMI, and D-Sub (VGA)
- Standard VESA mountable design
- Always allow you to join an online conference call with built-in speakers



1. 1x DisplayPort (1.2a)
2. 1x HDMI (1.4b)
3. 1x D-Sub (VGA)
4. 1x Line-in
5. 1x DC-in
6. 1x Kensington Lock

SPECIFICATION

Model	Part No	9S6-3PB4CH-087
	MKT Name	PRO MP273AW
	MKT Spec	PRO MP273AW
	Entity MKT Name	PRO MP273AW
	Color	ID1/White-White
Display	Screen Size	27" (69 cm)
	Active Display Area (mm)	597.888(H)x336.312(V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.3114(H)x0.3114(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	FreeSync
	Dynamic Refresh Rate Activated Range	48~100Hz
	HDR (High dynamic range)	N/A
	SDR Brightness (nits)	300
	Contrast Ratio	1000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	52.32~109 KHz (H) / 48~100 Hz(V)
	Refresh Rate	100HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	Response Time (Tr + Tf)	14ms
	View Angles	178°(H)/178°(V)
	Surface Treatment	Anti-glare
	NTSC (CIE1976 area percentage/overlap)	93%/83%
	NTSC (CIE1931 area percentage/overlap)	76%/74%
	sRGB (CIE1976 area percentage/overlap)	106%/99%
	sRGB (CIE1931 area percentage/overlap)	108%/99%
	Adobe RGB (CIE1976 area percentage/overlap)	91%/88%
	Adobe RGB (CIE1931 area percentage/overlap)	80%/77%
	DCI-P3 (CIE1976 area percentage/overlap)	85%/84%
	DCI-P3 (CIE1931 area percentage/overlap)	79%/79%
	Rec.709 (CIE1976 area percentage/overlap)	106%/99%
	Rec.709 (CIE1931 area percentage/overlap)	108%/99%
	Rec.2020 (CIE1976 area percentage/overlap)	61%/61%
	Rec.2020 (CIE1931 area percentage/overlap)	57%/57%
	Display Colors	16.7M
Color bit	8 bits (6 bits + FRC)	
I/O Ports	HDMI™	1
	HDMI™ version	1.4b
	HDMI™ HDCP version	1.4
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	1.3
	D-Sub	1
	Line-in	1
	Lock type	Kensington Lock
	Speaker	2
I/O Ports (Rear)	Card Reader	N/A
Power	Annual Energy Consumption (KWh)	21W
	Power Type	External Adaptor 12V 2.5A
	Power Input	100~240V, 50/60Hz
	Energy Efficiency Rating	E
	Adapter's KC safety Number	HU10450-16075
	Power Cord Type	C13
	QC Output Power	N/A
PD Output Power	N/A	

In The Box	3.5mm Mic Cable	0
	Switch Case	0
	Portable Screen Protection Case	0
	Monitor Hood	0
	Speaker (Accessories)	0
	DisplayPort Cable	0
	HDMI™ Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	Mouse Bungee Unit	0
	VESA Screw	0
	Power Cord	1
	AC Adaptor	1
	Warranty Card	0
Quick Guide	1	
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	75x75mm
	Frameless Design	Yes
Dimension & Weight	Inside Carton Dimension (WxDxH) (inch)	27.05 x 4.69 x 18.03
	Weight (Net kg)	3.9
	Weight (Gross kg)	5.3
Product Dimension with Stand (WxDxH)	Product Dimension with Stand (WxDxH) (mm)	613.50 x 182.0 x 461.6
	Product Dimension with Stand (WxDxH) (inch)	24.15 x 7.17 x 18.17
Stand Dimension (WxDxH)	Stand Dimension (WxDxH) (mm)	236.9 x 182.0 x 177.7
	Stand Dimension (WxDxH) (inch)	9.33 x 7.17 x 7.
Product Dimension without Stand (WxDxH)	Product Dimension without Stand (WxDxH) (mm)	613.50 x 48.5 x 362.5
	Product Dimension without Stand (WxDxH) (inch)	24.15 x 1.91 x 14.27
Outer Carton Dimension (WxDxH)	Outer Carton Dimension (WxDxH) (inch)	27.64 x 5.2 x 18.98
Weight	Weight Without Stand (kg)	3.4
Warranty	Warranty	36M
Barcode Info	EAN	4711377089203
	UPC	824142320600
	UCC14	10824142320607