ViewSonic

จอมอนิเตอร์แอลอีดี
TD2223-2

คีย์ คุณสมบัติ

- Intuitive 10-point touchscreen
- Finger, stylus, and glove touch compatible
- Magnetic pen placeholder
- Adjustable back tilt up to 40-degrees
- Scratch-resistant 7H hardness screen

สินค้า รายละเอียด

The ViewSonic® TD2223-2 is a 22" IR touch display designed for intuitive multi-touch use. Infrared (IR) touchscreen can detect up to 10 points of contact compared to optical touchscreens and can be operated by a stylus, fingers and gloved hands. The multi-touch input is more accurate, and the display is faster. Coupled with an adjustable tilt, you can easily interact with the TD2223-2 at an ideal position. This monitor features Full HD resolution to give you clear images and is built with scratch-resistant 7H hardness screen to surface damage. To support your work, the TD2223-2 is equipped with VGA, HDMI, DVI and USB connectivity.

เยี่ยมชม เรา   www.viewsonic.com

DISPLAY

Display Size (in.):	22
Viewable Area (in.):	21.5
Panel Type:	VA Technology
Resolution:	1920 x 1080
Resolution Type:	FHD (Full HD)
Static Contrast Ratio:	3,000:1 (typ)
Dynamic Contrast Ratio:	20M:1
Light Source:	LED
Brightness:	250 cd/m² (typ)
Colors:	16.7M
Color Space Support:	8 bit true
Aspect Ratio:	16:9
Response Time (Typical GTG):	6.5ms
Response Time (GTG w/OD):	6.5ms
Viewing Angles:	178º horizontal, 178º vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	75
Low Blue Light:	Software solution
Flicker-Free:	Yes
Color Gamut:	NTSC: 72% size (Typ) sRGB: 104% size (Typ)
Pixel Size:	0.249 mm (H) x 0.241 mm (V)
Touch Screen:	IR, 10-point multi-touch
Surface Treatment:	Glossy, Hard Coating (7H)
Cover Glass Thickness:	2mm

COMPATIBILITY

PC Resolution (max):	1920x1080
Mac® Resolution (max):	1920x1080
PC Operating System:	Windows 10/11 certified; macOS tested
Mac® Resolution (min):	1920x1080

CONNECTOR

VGA:	1
USB 2.0 Type A:	2
USB 2.0 Type B:	1
3.5mm Audio In:	1
3.5mm Audio Out:	1
HDMI 1.4:	1
DVI-D:	1
Power in:	3-pin Socket (IEC C14 / CEE22)

AUDIO

Internal Speakers:	2Watts x2

POWER

Eco Mode (Conserve):	13W
Eco Mode (optimized):	16W
Consumption (typical):	18.5W
Consumption (max):	21.8W
Voltage:	AC 100-240V
Stand-by:	0.5W
Power Supply:	Internal Power Supply

ADDITIONAL HARDWARE

Kensington Lock Slot:	1
Cable Organization:	Yes

CONTROLS

Physical Controls:	1, 2, Up, Down, Power
On Screen Display:	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Setup Menu, Memory Recall

OPERATING CONDITIONS

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

WALL MOUNT

VESA Compatible:	100 x 100 mm

INPUT SIGNAL

Frequency Horizontal:	RGB Analog: 24 ~ 82KHz, DVI-D: 24 ~ 82KHz, HDMI (v1.4): 25 ~ 85KHz
Frequency Vertical:	RGB Analog: 50 ~ 75Hz, DVI-D: 50 ~ 75Hz, HDMI (v1.4): 50 ~ 75Hz

VIDEO INPUT

Digital Sync:	TMDS - DVI-D, TMDS - HDMI (v1.4)
Analog Sync:	Separate/Composite/SOG - RGB Analog

ERGONOMICS

Tilt (Forward/Back):	20º / 40º

WEIGHT (IMPERIAL)

Net (lbs):	9.3
Net Without Stand (lbs):	8
Gross (lbs):	12.6

WEIGHT (METRIC)

Net (kg):	4.2
Net Without Stand (kg):	3.7
Gross (kg):	5.7

DIMENSIONS (IMPERIAL) (WXHXD)

Packaging (in.):	22.8 x 15.9 x 6.4
Physical (in.):	20.4 x 12.9 x 4
Physical Without Stand (in.):	20.4 x 12.1 x 2.4

DIMENSIONS (METRIC) (WXHXD)

Packaging (mm):	580 x 405 x 162
Physical (mm):	519 x 329 x 101
Physical Without Stand (mm):	519 x 308 x 61

GENERAL

Regulations:	cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NOM, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, BSMI, RCM, GEMS, VCCI, PSE, BIS
PACKAGE CONTENTS:	TD2223-2 x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male-Male) x1, USB A/B Cable (v2.0; Male-Male) x1, Audio Cable (Male-Male) x1, Quick Start Guide x1
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Warranty:	*Warranty offered may differ from market to market
Power Management:	Energy Star standards, EPEAT