

คีย์ คุณสมบัติ

- Intuitive 10-point touchscreen
- Finger, stylus, and glove touch compatible
- Magnetic pen placeholder
- Adjustable back tilt up to 40-degrees
- Scratch-resistant 7H hardness screen



สินค้า **รายละเอียด**

The ViewSonic® TD2423 is a 24" IR touch display designed for intuitive multi-touch use. Infrared (IR) touchscreen can detect up to 10 points of contact compared to optical touchscreens and can be operated by a stylus, fingers and gloved hands. The multi-touch input is more accurate, and the display is faster. Coupled with an adjustable tilt, you can easily interact with the TD2423 at an ideal position. This monitor features Full HD resolution to give you clear images and is built with scratch-resistant 7H hardness screen to surface damage. To support your work, the TD2423 is equipped with VGA, HDMI, DVI and USB connectivity.



เยี่ยมชม เรา

www.viewsonic.com

DISPLAY		ADDITIONAL HARDWARE	
Display Size (in.):	24	Kensington Lock Slot:	1
Viewable Area (in.):	23.6	Cable Organization:	Yes
Panel Type:	VA Technology	CONTROLS	
Resolution:	1920 x 1080	Physical Controls:	1, 2, Up, Down, Power
Resolution Type:	FHD (Full HD)	,	Auto Image Adjust,
Static Contrast Ratio:	3,000:1 (typ)	Contrast/Brightness, Input Sele On Screen Display: Audio Adjust, Color Adjust,	Contrast/Brightness, Input Select,
	20M:1		Information, Manual Image Adjust,
Dynamic Contrast Ratio:	LED	OPERATING CONDITIONS	Setup Menu, Memory Recall
Light Source:		Temperature:	32°F to 104°F (0°C to 40°C)
Brightness:	250 cd/m² (typ)	· ·	
Colors:	16.7M	Humidity (non-condensing): WALL MOUNT	20% to 90%
Color Space Support:	8 bit (6 bit + Hi-FRC)	VESA Compatible:	100 x 100 mm
Aspect Ratio:	16:9	INPUT SIGNAL	100 x 100 mm
Response Time (Typical GTG):	7ms	Frequency Horizontal:	24 ~ 82KHz
Response Time (GTG w/OD):	7ms		50 ~ 75Hz
Response Time (Typical Tr+Tf):	25ms	Frequency Vertical:	50 ~ 75HZ
Viewing Angles:	178° horizontal, 178° vertical	VIDEO INPUT	TMDS DVID TMDS HDMI (v4.4)
Backlight Life (Hours):	40000 Hrs (Min)	Digital Sync:	TMDS - DVI-D, TMDS - HDMI (v1.4)
Curvature:	Flat	Analog Sync:	Separate/Composite/SOG - RGB Analog
Refresh Rate (Hz):	75	ERGONOMICS	
Low Blue Light:	Software solution	Tilt (Forward/Back):	20° / 40°
Flicker-Free:	Yes	WEIGHT (IMPERIAL)	
Color Gamut:	NTSC: 72% size (Typ) sRGB: 104%	Net (lbs):	11.5
D. 10	size (Typ)	Net Without Stand (lbs):	10.3
Pixel Size:	0.272 mm (H) x 0.272 mm (V)	Gross (lbs):	15.4
Touch Screen:	IR, 10-point multi-touch	WEIGHT (METRIC)	
Surface Treatment:	Glossy, Hard Coating (7H)	Net (kg):	5.2
Cover Glass Thickness:	1.85mm	Net Without Stand (kg):	4.7
COMPATIBILITY		Gross (kg):	7
PC Resolution (max):	1920x1080	DIMENSIONS (IMPERIAL) (WXHXD)	
Mac® Resolution (max):	1920x1080	Packaging (in.):	25.4 x 16.6 x 6.5
PC Operating System:	Windows 7/8.1/10/11 certified; macOS tested	Physical (in.):	22.5 x 13.7 x 4
Mac® Resolution (min):	1920x1080	Physical Without Stand (in.):	22.5 x 13.7 x 2.4
CONNECTOR		DIMENSIONS (METRIC) (WXI	HXD)
VGA:	1	Packaging (mm):	645 x 422 x 166
USB 2.0 Type A:	2	Physical (mm):	571 x 348 x 101
USB 2.0 Type B:	1	Physical Without Stand (mm):	571 x 348 x 61
3.5mm Audio In:	1	GENERAL	
3.5mm Audio Out:	1	Regulations:	cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, MX-CoC, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, RCM, GEMS, VCCI, PSE, BIS, CCC, China RoHS, China Energy Label, CECP
HDMI 1.4:	1		
DVI-D:			
Power in:	3-pin Socket (IEC C14 / CEE22)		
AUDIO	3-piii 30cket (IEC C14 / CEE22)		TD2423 x1, 3-pin Plug (IEC C13 /
Internal Speakers:	2Watts x2	PACKAGE CONTENTS:	CEE22) x1, HDMI Cable (v1.4; Male- Male) x1, USB A/B Cable (v2.0; Male- Male) x1, Audio Cable (Male-Male)
POWER	Livello AL	MONAGE CONTENTS.	
Eco Mode (Conserve):	11.5W		x1, Quick Start Guide x1
Eco Mode (optimized):	13.5W	Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Consumption (typical):	15.5W	Warranty:	*Warranty offered may differ from
. (). ,		· _ ·	market to market
Consumption (max):	16.5W	Power Management:	Energy Star standards, EPEAT
Voltage:	AC 100-240V		
Stand-by:	0.5W		
Power Supply:	Internal Power Supply		

Copyright © ViewSonic Corporation 2000-2024. All rights reserved.