



จอมอนิเตอร์แอลอีดี

VA2201-H

คีย์ คุณสมบัติ

- SuperClear® VA panel
- 75Hz Refresh rate delivers fluid visuals
- Eye-care technology for comfortable viewing
- Various ViewMode color rendering options
- HDMI and VGA Input for flexible connectivity



สินค้า รายละเอียด

The ViewSonic VA2201-H is a 22" Full HD monitor featuring HDMI and VGA input for business or home usage. The optimal screen performance and comfortable viewing without tearing or stuttering is delivered through variable refresh rate, eye-care technology, and various ViewMode presets. Experience truly seamless multitasking on just one screen with a VESA-compatible mount at a low power consumption.



1. Menu Control Panel
2. VESA Compatible(Wall Mount 100 x 100mm)
3. HDMI
4. VGA
5. DC in

เยี่ยมชม เรา

www.viewsonic.com

DISPLAY

Display Size (in.):	22
Viewable Area (in.):	21.5
Panel Type:	VA Technology
Resolution:	1920 x 1080
Resolution Type:	FHD (Full HD)
Static Contrast Ratio:	3,000:1 (typ)
Dynamic Contrast Ratio:	50M:1
Light Source:	LED
Brightness:	250 cd/m ² (typ)
Colors:	16.7M
Color Space Support:	8 bit true
Aspect Ratio:	16:9
Response Time (MPRT):	1ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	100
Variable Refresh Rate Technology:	Yes
Low Blue Light:	Software solution
Flicker-Free:	Yes
Color Gamut:	NTSC: 72% size (Typ) sRGB: 104% size (Typ)
Pixel Size:	0.249 mm (H) x 0.241 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

COMPATIBILITY

PC Resolution (max):	1920x1080
Mac® Resolution (max):	1920x1080
PC Operating System:	Windows 10/11 certified; macOS tested
Mac® Resolution (min):	1920x1080

CONNECTOR

VGA:	1
3.5mm Audio Out:	1
HDMI 1.4:	1
Power in:	DC Socket (Center Positive)

POWER

Eco Mode (Conserve):	15W
Eco Mode (optimized):	18W
Consumption (typical):	22W
Consumption (max):	24W
Voltage:	AC 100-240V
Stand-by:	0.5W
Power Supply:	External Power Adaptor

ADDITIONAL HARDWARE

Kensington Lock Slot:	1
-----------------------	---

CONTROLS

Physical Controls:	Key 1 (favorite), Key 2, Key 3 (power), Key 4, Key 5
On Screen Display:	Input Select, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

OPERATING CONDITIONS

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

WALL MOUNT

VESA Compatible:	100 x 100 mm
------------------	--------------

INPUT SIGNAL

Frequency Horizontal:	RGB Analog: 24 ~ 86KHz, HDMI (v1.4): 30 ~ 115KHz
Frequency Vertical:	RGB Analog: 48 ~ 75Hz, HDMI (v1.4): 48 ~ 100Hz

VIDEO INPUT

Digital Sync:	TMDS - HDMI (v1.4)
Analog Sync:	Separate - RGB Analog

ERGONOMICS

Tilt (Forward/Back):	-3° / 20°
----------------------	-----------

WEIGHT (IMPERIAL)

Net (lbs):	5.3
Net Without Stand (lbs):	4.9
Gross (lbs):	7.7

WEIGHT (METRIC)

Net (kg):	2.4
Net Without Stand (kg):	2.2
Gross (kg):	3.5

DIMENSIONS (IMPERIAL) (WXHXD)

Packaging (in.):	21.9 x 13.8 x 4.7
Physical (in.):	19.4 x 14.4 x 6.5
Physical Without Stand (in.):	19.4 x 11.3 x 1.6

DIMENSIONS (METRIC) (WXHXD)

Packaging (mm):	555 x 350 x 120
Physical (mm):	492 x 367 x 165
Physical Without Stand (mm):	492 x 288 x 40

GENERAL

Regulations:	REACH, WEEE
PACKAGE CONTENTS:	VA2201-H x1, HDMI Cable (v1.4; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Warranty:	*Warranty offered may differ from market to market