## คีย์ คุณสมบัติ

- OLED TECH: True Black with 1.07 Billion colors (10Bit)
- Real and Surreal: 100 % DCI-P3
   Pantone Validated color coverage
   with Delta E < 2 as color quality</p>
   guarantee
- Create Anywhere You Want:
   Tripod ready and foldable stand for outdoor shooting and indoor review
- Instant View: Camera ready
   (Micro HDMI) and USB-C charging that brings your creative
   workstation wherever you are
- Integrated hood: Foldaway hood attaches instantly when you need to eliminate ambient light



## สินค้า รายละเอียด

Introducing industry-leading VP16-OLED with 1.07 Billion colors (10Bit). Merging what's real with the surreal, it boasts 100 % DCI-P3 Pantone Validated color coverage with Delta E < 2 as the color quality guarantee. Tripod-ready, VP16-OLED comes equipped with a foldable stand allowing you to perform your best in both indoor and outdoor settings. "Go dark" at any moment with a foldaway attachable hood that instantly eliminates any ambient light. Take your creative workstation no matter where you go and review the immediate results of your work, connecting your camera to the VP16-OLED via Micro HDMI and charging it effortlessly through USB-C connectivity.

เยี่ยมชม เรา

www.viewsonic.com

11	THE VETO-OLED 13.0 OL	ED Portable Monitor - แผนขอมูล - ว.	เมนค บารเทคเทย
DISPLAY		CONTROLS	
Display Size (in.):	16	Physical Controls:	Up, Down, Left/Return, Right/Confirmed, Power
Viewable Area (in.):	15.6		
Panel Type:	OLED Technology	On Screen Display:  OPERATING CONDITIONS	Input Select, Color Mode, ViewMode, Audio Adjust, Setup Menu
Resolution:	1920 x 1080		
Resolution Type:	FHD (Full HD)		
Static Contrast Ratio:	100,000:1 (typ)	OPERATING CONDITIONS	32°F to 104°F (0°C to
Dynamic Contrast Ratio:	20M:1	Temperature:	40°C)
Brightness:	400 cd/m² (typ)	Humidity (non-condensing):	20% to 90%
Colors:	1.07B	INPUT SIGNAL	
Color Space Support:	10 bit (8 bit + FRC)	Frequency Horizontal:	24 ~ 83KHz
Aspect Ratio:	16:9	Frequency Vertical:	50 ~ 61Hz
Response Time (Typical Tr+Tf):	1ms	VIDEO INPUT	
Viewing Angles:	170° horizontal, 170° vertical	Digital Sync:	TMDS - micro HDMI (v1.4), Micro-Packet - Type C
Backlight Life (Hours):	N/A Hrs (Min)	ERGONOMICS	71 -
Curvature:	Flat	Tilt (Forward/Back):	-60° / 20°
Refresh Rate (Hz):	60	WEIGHT (IMPERIAL)	
Low Blue Light:	Software solution	Net (lbs):	2.2
Color Gamut:	Adobe RGB: 112% size / 96% coverage (Typ) DCI-P3: 111% size /	Net Without Stand (lbs):	2.2
		Gross (lbs):	4.8
	100% coverage (Typ) EBU: 149% size /	WEIGHT (METRIC)	
	100% coverage (Typ) REC709: 150% size / 100% coverage (Typ) SMPTE-C: 163% size / 100% coverage (Typ) NTSC: 107% size (Typ) sRGB: 150% size / 100% coverage (Typ)	Net (kg):	0.98
		Net Without Stand (kg):	0.98
		Gross (kg):	2.2
		DIMENSIONS (IMPERIAL) (WXHXD)	
	0.179 mm (H) x 0.179	Packaging (in.):	16.3 x 12.3 x 3.5
Pixel Size:	mm (V)  Glare, Hard Coating	Physical (in.):	14.1 x 8.92~12.38 x 0.8
Surface Treatment:	(N/A)	Physical Without Stand (in.):	14.1 x 8.9 x 0.2
COMPATIBILITY		DIMENSIONS (METRIC) (WXHXD)	
PC Resolution (max):	1920x1080	Packaging (mm):	415 x 312 x 90
Mac® Resolution (max):	1920x1080 Windows 10/11	Physical (mm):	359 x 226.682~314.48 x 19
PC Operating System:	certified; macOS tested	Physical Without Stand (mm):	359 x 227 x 6
Mac® Resolution (min):	1920x1080	GENERAL	
CONNECTOR  USB 3.2 Type C Up Stream;  DisplayPort Alt mode :	2 (40W power charger)	Regulations:	cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NRCan, NOM, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UKrSEPRO, BSMI, RCM, GEMS, BIS
3.5mm Audio Out:	1		
Micro HDMI 1.4 In:	1		
Power in:	USB Type C (with video & data)		
AUDIO			VP16-OLED x1, micro HDMI Cable (v1.4; Male-Male) x1, USB Type-C Cable (Male- Male) x1, USB Type-C to Type-A 3.2 Gen1 Cable (Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Hood x1
Internal Speakers:	1Watts x2		
POWER		PACKAGE CONTENTS:	
Eco Mode (Conserve):	5W		
Eco Mode (optimized):	6W		
Consumption (typical):	7W		Please dispose of in
Consumption (max):	15W	Recycle/Disposal:	accordance with local, state or federal laws.
Voltage:	AC 100-240V		
Stand-by:	0.5W	Warranty:	*Warranty offered may differ from market to market

Power Supply: External Power Adaptor Power Management: Energy Star standards, EPEAT

Copyright © ViewSonic Corporation 2000-2024. All rights reserved.