

# ViewSonic® จอมอนิเตอร์แอลอีดี

## VP2756-4K

### คีย์ คุณสมบัติ

- **Lifelike True Beauty:** International color standard Pantone validated and 100% sRGB wide color gamut
- **Precise Color:** ColorPro Verified with pre-factory calibration for overwhelmed Delta E < 2 color accuracy
- **Multimedia Devices:** Support USB-C with 60W high-speed charging, plus HDMI 2.0, DisplayPort 1.2a, USB3.2
- **Unlimited Flexibility:** Auto Pivot & Ergonomic Stand with tilt, swivel, pivot, and height adjustments
- **The Visible Difference:** 4K UHD(3840\* 2160) resolution IPS panel with 27" frameless design



### สินค้า รายละเอียด

Designed with creative professionals in mind, the ViewSonic VP2756-4k delivers stunning true-to-life colors on screen. Pantone validated 100% sRGB coverage provides precise color reproduction, ensuring your work looks how it should, every time. A USB-C port that easily connects with your devices for easy charging and data transfer. Ergonomic engineering gives you the flexibility to do more without injury, while Auto Pivot lets shift between horizontal and vertical orientations effortlessly, letting your work be viewed how it's supposed to be.

เยี่ยมชม เรา

[www.viewsonic.com](http://www.viewsonic.com)

**DISPLAY**

|                              |  |
|------------------------------|--|
| Display Size (in.):          | 27   |
| Viewable Area (in.):         | 27   |
| Panel Type:                  | IPS Technology   |
| Resolution:                  | 3840 x 2160  |
| Resolution Type:             | UHD (Ultra HD)   |
| Static Contrast Ratio:       | 1,000:1 (typ)  |
| Dynamic Contrast Ratio:      | 20M:1  |
| Light Source:                | LED  |
| Brightness:                  | 350 cd/m <sup>2</sup> (typ)  |
| Colors:                      | 1.07B  |
| Color Space Support:         | 10 bit (8 bit + A-FRC)   |
| Aspect Ratio:                | 16:9   |
| Response Time (Typical GTG): | 5ms  |
| Response Time (GTG w/OD):    | 5ms  |
| Viewing Angles:              | 178° horizontal, 178° vertical   |
| Backlight Life (Hours):      | 30000 Hrs (Min)  |
| Curvature:                   | Flat   |
| Refresh Rate (Hz):           | 60   |
| Low Blue Light:              | Software solution  |
| Flicker-Free:                | Yes  |
| Color Gamut:                 | Adobe RGB: 81% size / 78% coverage (Typ) DCI-P3: 80% size / 80% coverage (Typ) EBU: 108% size / 98% coverage (Typ) REC709: 109% size / 100% coverage (Typ) SMPTE-C: 118% size / 100% coverage (Typ) NTSC: 77% size (Typ) sRGB: 109% size / 100% coverage (Typ) |
| Pixel Size:                  | 0.155 mm (H) x 0.155 mm (V)  |
| Surface Treatment:           | Anti-Glare, Hard Coating (3H)  |

**COMPATIBILITY**

|                        |                                       |
|------------------------|---------------------------------------|
| PC Resolution (max):   | 3840x2160                             |
| Mac® Resolution (max): | 3840x2160                             |
| PC Operating System:   | Windows 10/11 certified; macOS tested |
| Mac® Resolution (min): | 3840x2160                             |

**CONNECTOR**

|  |                                |
|--|--------------------------------|
| USB 3.2 Type A Down Stream:                      | 2                              |
| USB 3.2 Type B Up Stream:                        | 1                              |
| USB 3.2 Type C Up Stream; DisplayPort Alt mode : | 1 (60W power charger)          |
| HDMI 2.0 (with HDCP 2.2):                        | 2                              |
| DisplayPort:                                     | 1                              |
| Power in:  | 3-pin Socket (IEC C14 / CEE22) |

**AUDIO**

|                    |           |
|--------------------|-----------|
| Internal Speakers: | 2Watts x2 |
|--------------------|-----------|

**POWER**

|                        |                       |
|------------------------|-----------------------|
| Eco Mode (Conserve):   | 19.3W                 |
| Eco Mode (optimized):  | 21.5W                 |
| Consumption (typical): | 24W                   |
| Consumption (max):     | 28W                   |
| Voltage:               | AC 100-240V           |
| Stand-by:              | 0.3W                  |
| Power Supply:          | Internal Power Supply |

**ADDITIONAL HARDWARE**

|                       |     |
|-----------------------|-----|
| Kensington Lock Slot: | 1   |
| Cable Organization:   | Yes |

**CONTROLS**

|                    |   |
|--------------------|---|
| Physical Controls: | Key 1, Key 2, Key 3, Key 4, Key 5, Key 6 (power)                                    |
| On Screen Display: | Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu |

**OPERATING CONDITIONS**

|                            |                             |
|----------------------------|-----------------------------|
| Temperature:               | 32°F to 104°F (0°C to 40°C) |
| Humidity (non-condensing): | 20% to 90%                  |

**WALL MOUNT**

|                  |              |
|------------------|--------------|
| VESA Compatible: | 100 x 100 mm |
|------------------|--------------|

**INPUT SIGNAL**

|                       |             |
|-----------------------|-------------|
| Frequency Horizontal: | 15 ~ 136KHz |
| Frequency Vertical:   | 24 ~ 75Hz   |

**VIDEO INPUT**

|               |   |
|---------------|---|
| Digital Sync: | TMDS - HDMI (v2.0), PCI-E - DisplayPort (v1.2), Micro-Packet - Type C |
|---------------|---|

**ERGONOMICS**

|                      |           |
|----------------------|-----------|
| Height Adjust (mm):  | 130       |
| Swivel:              | 120°      |
| Tilt (Forward/Back): | -5° / 21° |
| Pivot (Right/Left):  | 90° / 90° |

**WEIGHT (IMPERIAL)**

|                          |      |
|--------------------------|------|
| Net (lbs):               | 16.6 |
| Net Without Stand (lbs): | 11.2 |
| Gross (lbs):             | 22.5 |

**WEIGHT (METRIC)**

|                         |      |
|-------------------------|------|
| Net (kg):               | 7.5  |
| Net Without Stand (kg): | 5.1  |
| Gross (kg):             | 10.2 |

**DIMENSIONS (IMPERIAL) (WXHxD)**

|                               |                          |
|-------------------------------|--------------------------|
| Packaging (in.):              | 29.1 x 18.3 x 8.9        |
| Physical (in.):               | 24.1 x 16.15~21.27 x 8.5 |
| Physical Without Stand (in.): | 24.1 x 14.3 x 2.1        |

**DIMENSIONS (METRIC) (WXHxD)**

|                              |                           |
|------------------------------|---------------------------|
| Packaging (mm):              | 740 x 465 x 225           |
| Physical (mm):               | 613 x 410.31~540.31 x 215 |
| Physical Without Stand (mm): | 613 x 363 x 53            |

**GENERAL**

|              |  |
|--------------|--|
| Regulations: | cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NOM, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, BIS, CCC, China RoHS, China Energy Label, CECP |
|--------------|--|

|                   |   |
|-------------------|---|
| PACKAGE CONTENTS: | VP2756-4K x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v2.0; Male-Male) x1, USB Type-C Cable (Male-Male) x1, USB A/B Cable (v3.2; Male-Male) x1, Quick Start Guide x1 |
|-------------------|---|

|                   |  |
|-------------------|--|
| Recycle/Disposal: | Please dispose of in accordance with local, state or federal laws. |
|-------------------|--|

|           |  |
|-----------|--|
| Warranty: | *Warranty offered may differ from market to market |
|-----------|--|

|                   |                              |
|-------------------|------------------------------|
| Power Management: | Energy Star standards, EPEAT |
|-------------------|------------------------------|