

ViewSonic® จอมอนิเตอร์แอลอีดี

VP2776

คีย์ คุณสมบัติ

- **Apple Compatible:** MAC Ready with 90W USB-C connectivity plus 95% DCI-P3 International Digital Film Standard color gamut
- **Hollywood Color:** VESA verified HDR400 with Nano IPS meets big screen standards for Cinematic quality.
- **Great for B-Roll:** 165 Hz Refresh Rate ideal for stellar sequences
- **Instant Color Adjustment:** Our exclusive ColorPro Wheel puts color calibration and adjustments at your fingertips with Adobe Software and on-screen displays
- **Portable Darkroom:** Foldaway hood attaches instantly to eliminate ambient light when you need to "go dark"



สินค้า รายละเอียด

Introducing the world's first professional monitor with an integrated color calibrator plus Nano IPS Color Gamut, 95% DCI-P3 capability & 165Hz refresh rate. Outstanding visual performance and unmatched color capability combine with award-winning ergonomic design and fingertip controls in our ColorPro VP76 Series Professional Monitors from ViewSonic. Designed exclusively to meet the visual needs of world-class photographers, vloggers, video editors, animators and game designers, ColorPro stands apart through a marriage of the latest tech and human touch. With integrated access to Adobe and Capture One editing software, ColorPro was created to surpass your expectations through a combination of elegant design, outstanding technology and a simple, intuitive interface for easy color adjustment.

เยี่ยมชม เรา

www.viewsonic.com

DISPLAY		POWER		GENERAL	
Display Size (in.):	27	Eco Mode (Conserve):	33.4W	Regulations:	
Viewable Area (in.):	27	Eco Mode (optimized):	36.3W		
Panel Type:	IPS Technology	Consumption (typical):	39.5W		
Resolution:	2560 x 1440	Consumption (max):	43.5W	PACKAGE CONTENTS	
Resolution Type:	QHD (Quad HD)	Voltage:	AC 100-240V		
Static Contrast Ratio:	1,000:1 (typ)	Stand-by:	0.5W		
Dynamic Contrast Ratio:	20M:1	Power Supply:	Internal Power Supply	Recycle/Disposal:	
High Dynamic Range:	VESA HDR400	ADDITIONAL HARDWARE			
Light Source:	LED	Kensington Lock Slot:	1		
Brightness:	400 cd/m ² (typ)	Cable Organization:	Yes	Warranty:	
Colors:	1.07B	CONTROLS			
Color Space Support:	10 bit (8 bit + A-FRC)	Physical Controls:	Joystick key: Up, Right, Down, Left, Center; Power		
Aspect Ratio:	16:9	On Screen Display:	Input Select, Color Mode, ViewMode, Audio Adjust, Setup Menu	Power Management:	
Response Time (Typical GTG):	3ms	OPERATING CONDITIONS			
Response Time (GTG w/OD):	3ms	Temperature:	32°F to 104°F (0°C to 40°C)		
Response Time (MPRT):	1ms	Humidity (non-condensing):	20% to 90%	WALL MOUNT	
Viewing Angles:	178° horizontal, 178° vertical	INPUT SIGNAL			
Backlight Life (Hours):	30000 Hrs (Min)	VESA Compatible:	100 x 100 mm		
Curvature:	Flat	VIDEO INPUT		Digital Sync:	
Refresh Rate (Hz):	165	Frequency Horizontal:	HDMI (v2.0): 20 ~ 230KHz, DisplayPort (v1.4): 30 ~ 250KHz, Type C: 30 ~ 250KHz		
Variable Refresh Rate Technology:	G-Sync compatible	Frequency Vertical:	HDMI (v2.0): 48 ~ 144Hz, DisplayPort (v1.4): 48 ~ 165Hz, Type C: 48 ~ 165Hz		
Low Blue Light:	Software solution	ERGONOMICS		TMD5 - HDMI (v2.0), PCI-E - DisplayPort (v1.4), Micro-Packet - Type C	
Flicker-Free:	Yes	Height Adjust (mm):	120		
Color Gamut:	Adobe RGB: 99% size / 87% coverage (Typ) DCI-P3: 98% size / 95% coverage (Typ) EBU: 131% size / 100% coverage (Typ) REC709: 133% size / 100% coverage (Typ) SMPTE-C: 144% size / 100% coverage (Typ) NTSC: 94% size (Typ) sRGB: 133% size / 100% coverage (Typ)	Swivel:	120°		
Pixel Size:	0.233 mm (H) x 0.233 mm (V)	Tilt (Forward/Back):	-3° / 21°	Pivot (Right/Left): 90° / 90°	
Surface Treatment:	Anti-Glare, Hard Coating (3H)	WEIGHT (IMPERIAL)			
COMPATIBILITY		Net (lbs):	18.5		
PC Resolution (max):	2560x1440	Net Without Stand (lbs):	11.2	Gross (lbs): 28.2	
Mac® Resolution (max):	2560x1440	WEIGHT (METRIC)			
PC Operating System:	Windows 10/11 certified; macOS tested	Net (kg):	8.4		
Mac® Resolution (min):	2560x1440	Net Without Stand (kg):	5.1	Gross (kg): 12.8	
CONNECTOR		DIMENSIONS (IMPERIAL) (WXHxD)			
USB 3.1 Type C - Downstream:	1	Packaging (in.):	27.2 x 19.9 x 8.9		
USB 3.2 Type A Down Stream:	2	Physical (in.):	24.2 x 17.69~22.42 x 9.2	Physical Without Stand (in.): 24.2 x 14.3 x 2.1	
USB 3.2 Type B Up Stream:	1	DIMENSIONS (METRIC) (WXHxD)			
USB 3.2 Type C Up Stream; DisplayPort Alt mode :	1 (90W power charger)	Packaging (mm):	692 x 505 x 225		
Micro USB:	1	Physical (mm):	614 x 449.36~569.36 x 234	Physical Without Stand (mm): 614 x 364 x 54	
3.5mm Audio Out:	1	AUDIO			
HDMI 2.0 (with HDCP 2.2):	2	Internal Speakers:	3Watts x2		
DisplayPort:	1				
Power in:	3-pin Socket (IEC C14 / CEE22)				