



จอมอนิเตอร์แอลอีดี

VX2428

คีย์ คุณสมบัติ

- Fast IPS Display with HDR10
- AMD FreeSync™ Premium for smooth gameplay
- VESA AdaptiveSync for tear-free gaming experience
- VESA ClearMR for clarity of action
- Rapid 0.5ms MPRT for crisp image



สินค้า รายละเอียด

No matter how often you game or when you game, you always win with the Omni VX2428. The triple certification of AMD FreeSync™ Premium, VESA Adaptive Sync, and VESA clearMR allows you to savor distortion-free gaming and enhanced clarity. The sharp frames and outstanding color performance are delivered by a fast IPS panel, while the VX2428's high 180Hz refresh rate supports smooth visuals and minimal input lag. You may think it doesn't get better than this, but it does. Not only will you get the job done — be it grueling gaming sessions, video and photo editing, or office assignments — you'll be working on a sleek, beautifully designed monitor.

เยี่ยมชม เราwww.viewsonic.com

DISPLAY

Display Size (in.):	24
Viewable Area (in.):	23.8
Panel Type:	IPS Technology
Resolution:	1920 x 1080
Resolution Type:	FHD (Full HD)
Static Contrast Ratio:	1,000:1 (typ)
Dynamic Contrast Ratio:	80M:1
High Dynamic Range:	HDR10
Light Source:	LED
Brightness:	250 cd/m ² (typ)
Colors:	16.7M
Color Space Support:	8 bit (6 bit + FRC)
Aspect Ratio:	16:9
Response Time (MPRT):	0.5ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	180
Variable Refresh Rate Technology:	FreeSync Premium, AdaptiveSync
Low Blue Light:	Software solution
Flicker-Free:	Yes
Color Gamut:	NTSC: 72% size (Typ) sRGB: 104% size (Typ)
Pixel Size:	0.275 mm (H) x 0.275 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

COMPATIBILITY

PC Resolution (max):	1920x1080
Mac® Resolution (max):	1920x1080
PC Operating System:	Windows 10/11 certified; macOS tested
Mac® Resolution (min):	1920x1080

CONNECTOR

3.5mm Audio Out:	1
HDMI 1.4:	2
DisplayPort:	1
Power in:	DC Socket (Center Positive)

AUDIO

Internal Speakers:	2Watts x2
--------------------	-----------

POWER

Eco Mode (Conserve):	17W
Eco Mode (optimized):	20W
Consumption (typical):	24W
Consumption (max):	25W
Voltage:	AC 100-240V
Stand-by:	0.3W
Power Supply:	External Power Adaptor

ADDITIONAL HARDWARE**CONTROLS**

Physical Controls:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

OPERATING CONDITIONS

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

WALL MOUNT

VESA Compatible:	100 x 100 mm
------------------	--------------

INPUT SIGNAL

Frequency Horizontal:	HDMI (v1.4): 30 ~ 166KHz, DisplayPort (v1.4): 30 ~ 193KHz
Frequency Vertical:	HDMI (v1.4): 48 ~ 180Hz, DisplayPort (v1.4): 48 ~ 180Hz

VIDEO INPUT

Digital Sync:	TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.4)
---------------	--

ERGONOMICS

Tilt (Forward/Back):	-5° / 20°
----------------------	-----------

WEIGHT (IMPERIAL)

Net (lbs):	6.8
Net Without Stand (lbs):	6.1
Gross (lbs):	9.7

WEIGHT (METRIC)

Net (kg):	3.1
Net Without Stand (kg):	2.8
Gross (kg):	4.4

DIMENSIONS (IMPERIAL) (WXHxD)

Packaging (in.):	23.8 x 15.7 x 4.7
Physical (in.):	21.3 x 16.3 x 7.2
Physical Without Stand (in.):	21.3 x 12.7 x 1.7

DIMENSIONS (METRIC) (WXHxD)

Packaging (mm):	605 x 400 x 120
Physical (mm):	542 x 413 x 183
Physical Without Stand (mm):	542 x 323 x 44

GENERAL

Regulations:	cTUVus, FCC-B, ICES003, CEC, NRCAN, NOM, Mexico Energy, CE, CE EMC, LVD/CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, BSMI, RCM, GEMS, BIS
--------------	---

PACKAGE CONTENTS:	VX2428 x1, 3-pin Plug (IEC C13 / CEE22) x1, DisplayPort Cable (v1.2; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1
-------------------	--

Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
-------------------	--

Warranty:	*Warranty offered may differ from market to
-----------	---

Kensington Lock Slot:	1
-----------------------	---

Copyright © ViewSonic Corporation 2000-2024. All rights reserved.