

i ประกาศ : ข้อความที่เข้าขายน่าสงสัยจากบุคคลที่แอบอ้างถึงแคนนอน

1 of 2

Canon ประเทศไทย
Delighting You Always

สนับสนุน

f in 

iX6770 Specifications

อัปเดตล่าสุด: 30-ม.ค.-2014

หมายเลขการออก: 6200195900

General Specifications	
Printing resolution (dpi)	9600* (horizontal) x 2400 (vertical) * Ink droplets can be placed with a pitch of 1/9600 inch at minimum.
Interface	USB Port: Hi-Speed USB * * A computer that complies with Hi-Speed USB standard is required. Since the Hi-Speed USB interface is fully upwardly compatible with USB 1.1, it can be used at USB 1.1
Print width	12.7 inches/322.2 mm (for Borderless Printing: 13 inches/329 mm)
Operating environment	Temperature: 41 to 95 °F (5 to 35 °C) Humidity: 10 to 90 % RH (no condensation) * For the temperature and humidity conditions of papers such as photo paper, refer to the paper's packaging or the supplied instructions.
Storage environment	Temperature: 32 to 104 °F (0 to 40 °C) Humidity: 5 to 95 % RH (no condensation)
Power supply	AC 100-240 V, 50/60 Hz
Power consumption	Printing: Approx. 21 W Standby (minimum): Approx. 0.8 W *1*2 OFF: Approx. 0.2 W* 1 *1 USB connection to PC *2 The wait time for standby cannot be changed.
External dimensions	Approx. 23 (W) x 12.3 (D) x 6.3 (H) inches Approx. 584 (W) x 310 (D) x 159 (H) mm * With the Paper Support and Paper Output Tray retracted.

Weight	Approx. 17.8 lb (Approx. 8.1 kg) * With the Print Head and ink tanks installed.
Print Head/Ink	Total 5120 nozzles (PGBK 1024 nozzles, Y/DyeBK each 512 nozzles, C/M each 1536 nozzles)

ลิขสิทธิ์ © 2024 Canon Marketing (Thailand) Co., Ltd. จำกัด สงวนลิขสิทธิ์