ประกาศ : ข้อความที่เข้าข่ายน่าสงสัยจากบุคคลที่แอบอ้างถึงแคนนอน

1 of 2



สนับสนุน

f in 🕀

Specifications

<mark>อัพเดทล่าสุด:</mark> 29-พ.ค.-2014 หมายเลขการออก: 6200206200

Machine Specifications				
Hardware Specifications				
Туре	Desktop page printer			
Printing System	Semiconductor laser + dry-type electrophotographic system			
Toner Fixing System	On-demand fixing system			
Print Speed*1 (Plain paper (60 to 89 g/㎡), A4 continuous printing)	18 pages/minute			
Warm-Up Time*2 (from power ON until machine enters standby)	10 seconds or less			
Recovery Time*3 (recovery from sleep mode to standby)	1 second or less			
First Print Time*3 (A4 printing)	Approx. 7.8 seconds			
Paper Capacity (Multi-purpose tray)	Approx. 150 sheets			

Face down

Approx. 100 sheets

Due to continuing product enhancements, the specifications of this machine are subject to change without notice.

Paper Output Output Capacity*4

 (Output tray)
 Approx. 100 sheets

 Noise
 LwAd (declared A-weighted sound power level (measured in accordance with ISO 7779, declared noise emission in accordance with ISO 9296)
 LwAd (declared A-weighted sound power level (1 B = 10 dB))

 - During standby: Inaudible*5

	 During printing: 6.53 B or less LpAm (declared A-weighted sound pressure level (bystander position)) During standby: Inaudible*5 During printing: 49.3 B
Environmental Conditions (machine only)	Operating Environment - Temperature: 10 to 30 °C - Humidity: 20 to 80% RH (no condensation)
Host Interface	LBP6030w - USB interface: Hi-Speed USB/USB - Network interface: IEEE 802.11b/g/n LBP6030B / LBP6030 - USB interface: Hi-Speed USB/USB
User Interface	LBP6030w - LED indicators: 3 - Operation keys: 2 LBP6030B / LBP6030 - LED indicators: 2 - Operation keys: 1
Power	220 to 240 V (± 10 %), 50/60 Hz (± 2 Hz)
Power Consumption*6 (20 °C)	Maximum: 870 W or less During operation: Approx. 330 W During standby: - 1.8 W or less (USB connection) - 2.8 W or less (wireless LAN connection) (LBP6030w only) During sleep mode: - 0.8 W or less (USB connection) - 1.6 W or less (Wireless LAN connection) (LBP6030w only) When the power switch is turned OFF: 0.5 W or less
Consumables	Canon toner cartridge *7
Weight	Machine and accessories - Machine (excluding toner cartridge): Approx. 5.0 kg - Toner cartridge: Approx. 0.5 kg Consumables - Toner cartridge (Canon Genuine Cartridge): Approx. 0.5 kg

*1 Print speed may be slower depending on the settings for output adjustment mode, paper size and type, paper orientation, and number of copies printed.

*2 May vary depending on conditions of use (installation environment, etc.).

*3 May vary depending on the output environment.

*4 May vary depending on the installation environment and type of paper used.

*5 Indicates that the sound pressure level of each bystander position is below the ISO 7779 absolute criteria for the background noise level.

*6 Even if the machine is turned OFF, a slight amount of power is still consumed while the power plug is plugged into the AC power outlet. To stop power consumption completely, unplug the power plug from the AC power outlet. *7 For details on the yield, see the "e-Manual" (HTML manual) in the CD-ROM/DVD-ROM supplied with the printer.

■Software Specifications	
Printing Software	UFR II

Wireless LAN Specifications (LBP6030w)		
Standards	IEEE 802.11b/g/n	
Transmission Scheme	DS-SS system, OFDM system	
Frequency Range	2,412 to 2,472 MHz	
Data Transmission Rate	IEEE 802.11b - 1/2/5.5/11 Mbps IEEE 802.11g - 6/9/12/18/24/36/48/54 Mbps IEEE 802.11n - SGI Invalidated 20 MHz: 6.5/13/19.5/26/39/52/58.5/65 Mbps - SGI Validated 20 MHz: 7.2/14.4/21.7/28.9/43.3/57.8/72.2 Mbps - SGI Validated 40 MHz: 13.5/27/40.5/81/108/121.5/135 Mbps - SGI Validated 40 MHz: 15/30/45/60/90/120/150 Mbps	
Communication Mode	Infrastructure mode	
Security	WEP, WPA-PSK (TKIP/AES-CCMP), WPA2-PSK (TKIP/AES-CCMP)	
Connection Method WPS (Wi-Fi Protected Setup), Manual setup		

Paper

Supported Paper Sizes

Paper sizes that can be loaded in the multi-purpose tray are listed below.

A4 (210.0 mm x 297.0 mm) B5 (182.0 mm x 257.0 mm) A5 (148.5 mm x 210.0 mm) Legal (215.9 mm x 355.6 mm) Letter (215.9 mm x 279.4 mm) Executive (184.2 mm x 266.7 mm) Oficio (216.0 mm x 317.0 mm) Brazil Oficio (216.0 mm x 355.0 mm) Mexico Oficio (216.0 mm x 341.0 mm) Foolscap (216.0 mm x 330.0 mm) 16K (195.0 mm x 270.0 mm) Envelope Monarch (98.4 mm x 190.5 mm) Envelope No. 10 (COM10) (104.7 mm x 241.3 mm) Envelope DL (110.0 mm x 220.0 mm) Envelope C5 (162.0 mm x 229.0 mm) Custom paper size (Width 76.2 to 216.0 mm x Length 188.0 to 356.0 mm)

Paper Tray Capacity by Paper Type

Chlorine-free paper can be used with this machine.

Paper Type		Capacity (Multi-Purpose Tray)
Plain paper*1	60 to 80 g/m ²	Approx. 150 sheets
	81 to 89 g/m ²	Approx. 120 sheets
Heavy paper	90 to 105 g/m ²	Approx. 100 sheets
	106 to 163 g/m [*]	Approx. 60 sheets
Transparency*2*3		Approx. 100 sheets
Labels *3		Approx. 50 sheets
Envelope		Approx. 10 sheets

*1 Recycled paper can be used.

*2 Use laser printer transparencies.

*3 Use A4 or Letter size only.

Machine Settings for Paper Types

r Type	Printer Driver Paper Setting
60 to 63 g/m ²	[Plain L]
n paper *1 64 to 89 g/m ²	[Plain]
$00 \pm 1/2 = 1/2^2$	[Heavy]
90 to 103 g/m	[Heavy H]*2
*3 *4	[Transparency]
	[Labels]
	[Envelope]

*1 Recycled paper can be used.


*2 If toner is not fully fixed and printouts are faded when you select [Heavy], select this instead.

*3 Use laser printer transparencies.

*4 Use A4 or Letter size only.

Printable Range

The printable range is indicated in gray. Envelopes require a 10 mm margin on the top, bottom, left, and right.



ลิขสิทธิ์ © 2024 Canon Marketing (Thailand) Co., Ltd. จำกัด สงวนลิขสิทธิ์