

**i** สำนักงานย่อยบริษัท แคนนอน มาร์เก็ตติ้ง (ไทยแลนด์) จำกัด - อมตะซีดี จ.ชลบุรี จะย้ายที่ทำการสำนักงานฯ ไปยังสถานที่ใหม่ใน วันจันทร์ที่ 3 มิถุนายน 2567

2 of 2

**Canon** ประเทศไทย  
Delighting You Always

สนับสนุน

f in 

# Specifications

อัปเดตล่าสุด: 29-พ.ค.-2014

หมายเลขการออก: 6200206200

Due to continuing product enhancements, the specifications of this machine are subject to change without notice.

## Machine Specifications

### ■ Hardware Specifications

|  |   |
|--|---|
| Type   | Desktop page printer  |
| Printing System  | Semiconductor laser + dry-type electrophotographic system                                   |
| Toner Fixing System  | On-demand fixing system   |
| Print Speed*1<br>(Plain paper (60 to 89 g/m <sup>2</sup> ), A4 continuous printing)                  | 18 pages/minute   |
| Warm-Up Time*2<br>(from power ON until machine enters standby)                                       | 10 seconds or less  |
| Recovery Time*3<br>(recovery from sleep mode to standby)   | 1 second or less  |
| First Print Time*3<br>(A4 printing)  | Approx. 7.8 seconds   |
| Paper Capacity<br>(Multi-purpose tray)   | Approx. 150 sheets  |
| Paper Output   | Face down   |
| Output Capacity*4<br>(Output tray)   | Approx. 100 sheets  |
| Noise<br>(measured in accordance with ISO 7779, declared noise emission in accordance with ISO 9296) | LwAd (declared A-weighted sound power level (1 B = 10 dB))<br>- During standby: Inaudible*5 |

|   |   |
|---|---|
|   | <ul style="list-style-type: none"> <li>- During printing: 6.53 B or less LpAm (declared A-weighted sound pressure level (bystander position))</li> <li>- During standby: Inaudible*5</li> <li>- During printing: 49.3 B</li> </ul>  |
| Environmental Conditions (machine only) | <p>Operating Environment</p> <ul style="list-style-type: none"> <li>- Temperature: 10 to 30 °C</li> <li>- Humidity: 20 to 80% RH (no condensation)</li> </ul>   |
| Host Interface                          | <p>LBP6030w</p> <ul style="list-style-type: none"> <li>- USB interface: Hi-Speed USB/USB</li> <li>- Network interface: IEEE 802.11b/g/n</li> </ul> <p>LBP6030B / LBP6030</p> <ul style="list-style-type: none"> <li>- USB interface: Hi-Speed USB/USB</li> </ul>  |
| User Interface                          | <p>LBP6030w</p> <ul style="list-style-type: none"> <li>- LED indicators: 3</li> <li>- Operation keys: 2</li> </ul> <p>LBP6030B / LBP6030</p> <ul style="list-style-type: none"> <li>- LED indicators: 2</li> <li>- Operation keys: 1</li> </ul>   |
| Power                                   | 220 to 240 V (± 10 %), 50/60 Hz (± 2 Hz)  |
| Power Consumption*6 (20 °C)             | <p>Maximum: 870 W or less</p> <p>During operation: Approx. 330 W</p> <p>During standby:</p> <ul style="list-style-type: none"> <li>- 1.8 W or less (USB connection)</li> <li>- 2.8 W or less (wireless LAN connection) (LBP6030w only)</li> </ul> <p>During sleep mode:</p> <ul style="list-style-type: none"> <li>- 0.8 W or less (USB connection)</li> <li>- 1.6 W or less (wireless LAN connection) (LBP6030w only)</li> </ul> <p>When the power switch is turned OFF: 0.5 W or less</p> |
| Consumables                             | Canon toner cartridge *7  |
| Weight                                  | <p>Machine and accessories</p> <ul style="list-style-type: none"> <li>- Machine (excluding toner cartridge): Approx. 5.0 kg</li> <li>- Toner cartridge: Approx. 0.5 kg</li> </ul> <p>Consumables</p> <ul style="list-style-type: none"> <li>- Toner cartridge (Canon Genuine Cartridge): Approx. 0.5 kg</li> </ul>  |

\*1 Print speed may be slower depending on the settings for output adjustment mode, paper size and type, paper orientation, and number of copies printed.

\*2 May vary depending on conditions of use (installation environment, etc.).

\*3 May vary depending on the output environment.

\*4 May vary depending on the installation environment and type of paper used.

\*5 Indicates that the sound pressure level of each bystander position is below the ISO 7779 absolute criteria for the background noise level.

\*6 Even if the machine is turned OFF, a slight amount of power is still consumed while the power plug is plugged into the AC power outlet. To stop power consumption completely, unplug the power plug from the AC power outlet.

\*7 For details on the yield, see the "e-Manual" (HTML manual) in the CD-ROM/DVD-ROM supplied with the printer.

#### ■ Software Specifications

|                   |        |
|-------------------|--------|
| Printing Software | UFR II |
|-------------------|--------|

#### Wireless LAN Specifications (LBP6030w)

|                        |   |
|------------------------|---|
| Standards              | IEEE 802.11b/g/n  |
| Transmission Scheme    | DS-SS system, OFDM system   |
| Frequency Range        | 2,412 to 2,472 MHz  |
| Data Transmission Rate | IEEE 802.11b<br>- 1/2/5.5/11 Mbps<br>IEEE 802.11g<br>- 6/9/12/18/24/36/48/54 Mbps<br>IEEE 802.11n<br>- SGI Invalidated 20 MHz: 6.5/13/19.5/26/39/52/58.5/65 Mbps<br>- SGI Validated 20 MHz: 7.2/14.4/21.7/28.9/43.3/57.8/72.2 Mbps<br>- SGI Invalidated 40 MHz: 13.5/27/40.5/81/108/121.5/135 Mbps<br>- SGI Validated 40 MHz: 15/30/45/60/90/120/150 Mbps |
| Communication Mode     | Infrastructure mode   |
| Security               | WEP, WPA-PSK (TKIP/AES-CCMP), WPA2-PSK (TKIP/AES-CCMP)  |
| Connection Method      | WPS (Wi-Fi Protected Setup), Manual setup   |

#### Paper

##### ■ Supported Paper Sizes

Paper sizes that can be loaded in the multi-purpose tray are listed below.

A4 (210.0 mm x 297.0 mm)  
 B5 (182.0 mm x 257.0 mm)  
 A5 (148.5 mm x 210.0 mm)  
 Legal (215.9 mm x 355.6 mm)  
 Letter (215.9 mm x 279.4 mm)  
 Executive (184.2 mm x 266.7 mm)  
 Oficio (216.0 mm x 317.0 mm)  
 Brazil Oficio (216.0 mm x 355.0 mm)  
 Mexico Oficio (216.0 mm x 341.0 mm)  
 Foolscap (216.0 mm x 330.0 mm)  
 16K (195.0 mm x 270.0 mm)  
 Envelope Monarch (98.4 mm x 190.5 mm)  
 Envelope No. 10 (COM10) (104.7 mm x 241.3 mm)  
 Envelope DL (110.0 mm x 220.0 mm)  
 Envelope C5 (162.0 mm x 229.0 mm)  
 Custom paper size (Width 76.2 to 216.0 mm x Length 188.0 to 356.0 mm)

##### ■ Paper Tray Capacity by Paper Type

Chlorine-free paper can be used with this machine.

| Paper Type        |                             | Capacity (Multi-Purpose Tray) |
|-------------------|-----------------------------|-------------------------------|
| Plain paper*1     | 60 to 80 g/m <sup>2</sup>   | Approx. 150 sheets            |
|                   | 81 to 89 g/m <sup>2</sup>   | Approx. 120 sheets            |
| Heavy paper       | 90 to 105 g/m <sup>2</sup>  | Approx. 100 sheets            |
|                   | 106 to 163 g/m <sup>2</sup> | Approx. 60 sheets             |
| Transparency*2 *3 |                             | Approx. 100 sheets            |
| Labels *3         |                             | Approx. 50 sheets             |
| Envelope          |                             | Approx. 10 sheets             |

\*1 Recycled paper can be used.  
 \*2 Use laser printer transparencies.  
 \*3 Use A4 or Letter size only.

**Machine Settings for Paper Types**

| Paper Type         |                            | Printer Driver Paper Setting |
|--------------------|----------------------------|------------------------------|
| Plain paper *1     | 60 to 63 g/m <sup>2</sup>  | [Plain L]                    |
|                    | 64 to 89 g/m <sup>2</sup>  | [Plain]                      |
| Heavy paper        | 90 to 163 g/m <sup>2</sup> | [Heavy]                      |
|                    |                            | [Heavy H] *2                 |
| Transparency *3 *4 |                            | [Transparency]               |
| Labels *4          |                            | [Labels]                     |
| Envelope           |                            | [Envelope]                   |

\*1 Recycled paper can be used.  
 \*2 If toner is not fully fixed and printouts are faded when you select [Heavy], select this instead.  
 \*3 Use laser printer transparencies.  
 \*4 Use A4 or Letter size only.

**Printable Range**

The printable range is indicated in gray. Envelopes require a 10 mm margin on the top, bottom, left, and right.

---

ลิขสิทธิ์ © 2024 Canon Marketing (Thailand) Co., Ltd. จำกัด สงวนลิขสิทธิ์