GeForce RTX™ 4090 SUPRIM X 24G







SPECIFICATIONS

Memory	24GB GDDR6X
Graphics Engine	NVIDIA® GeForce RTX™ 4090
Bus Standard	PCI Express [®] Gen 4
Memory Interface	384-bit
Core Clock Speed(MHz)	Extreme Performance: 2640 MHz (MSI Center) Boost: 2625 MHz (GAMING & SILENT Mode)
Memory Clock Speed(MHz)	21 Gbps
Maximum Displays	4
G-SYNC™ technology	Υ
Output	DisplayPort x 3 (v1.4a) HDMI™ x 1 (Supports 4K @120Hz HDR, 8K@60Hz HDR, and Variable Refresh Rate as specified in HDMI™ 2.1a)
HDCP Support	Y
Power consumption (W)	Silent mode: 450W Gaming mode: 480W
Recommended Power Supply (W)	1000W (Min. 850W)
Digital Maximum Resolution	7680 x 4320
Power Connectors	16-pin x 1
DirectX Version Support	12 Ultimate
OpenGL Version Support	4.6
Card Dimension(mm)	336 x 142 x 78 mm
Weight	2413g / 3636g

CONNECTIONS



- 1. DisplayPort
- 2. HDMI™

FEATURES



TRI FROZR 3S

Push performance with the latest MSI cooling design and elevate sophistication with a prestigious appearance.



TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



Vapor Chamber

The GPU and memory modules are covered with a Vapor Chamber which rapidly transfers heat to Core Pipes.



Core Pipe

Precision-machined heat pipes ensure max contact to the GPU and spread heat along the full length of the heatsink.



Airflow Control

Sections of different heatsink fins disrupt unwanted airflow harmonics and reduce noise.



Zero Frozr

Zero Frozr is the calm before the storm, keeping fans still and maintaining silence until cooling is needed.



Aluminum Backplate

Thermal pads beneath the sturdy metal backplate provide additional cooling.



vave Curved 3.0

Additional efficiency is gained by adjusting the size of the wave edges under the fan motor and other spots where there is less airflow.