


**C994**

| Product Image   |                             | Features   |  |                   |   |
|---|-----------------------------|--|--|-------------------|---|
|  |                             | ★ F2.0 large aperture, more light intake, clearer night vision                       |  |                   |   |
|   |                             | ★ Infrared and white light integrated light board, supports full color day and night |  |                   |   |
|   |                             | ★ ISP image processing technology, preserving true colors                            |  |                   |   |
|   |                             | ★ Human detection, real time alerts  |  |                   |   |
| No.   | Sorts                       | Type   | Parameters   |                   |   |
| 1   | System                      | Operating system   | Linux  |                   |   |
|   |                             | Online visitor   | Supports 4 visitors at the same time   |                   |   |
|   |                             | APP  | O-KAM Pro  |                   |   |
| 2   | Collection                  | CPU  | Ingenic  |                   |   |
|   |                             | Memory   | 512Mb  |                   |   |
|   |                             | Lens   | 4mm  |                   |   |
|   |                             | Image sensor   | 1/4.5-inch high-quality 1-megapixel CMOS image sensor  |                   |   |
|   |                             | Min. Illumination  | 0.5Lux (color mode), 0.1Lux (b&w mode)   |                   |   |
|   |                             | Sensor performance   | Support automatic white balance, automatic gain control and automatic backlight compensation |                   |   |
|   |                             | Night vision   | Black and white night vision, full-color night vision  |                   |   |
| 3   | Video                       | Viewing angle  | Diagonal: 58°  |                   |   |
|   |                             | Resolution   | 720P 1280x720/15FPS/1MP; 1080P 1920x1080/15FPS/2MP   |                   |   |
|   |                             | Night vision   | Black and white night vision, full-color night vision  |                   |   |
|   |                             | Compression standard   | H.264 main profile/Motion-JPEG/JPEG  |                   |   |
|   |                             | IR control   | IR-CUT, soft photosensitive control  |                   |   |
|   |                             | Bit rate   | 128 ~ 4096kbps   |                   |   |
| 4   | Audio                       | Image adjustment   | Brightness, contrast, OSD display  |                   |   |
|   |                             | Input  | Built-in -38dB microphone  |                   |   |
|   |                             | Output   | Built-in 8Ω1W speaker  |                   |   |
|   |                             | Sampling frequency/bit width   | 8KHz/16bit   |                   |   |
| 5   | Pan/Tilt                    | Compression standard/Bit Rate  | G711A  |                   |   |
|   |                             | Rotation angle   | Horizontal: 325° Vertical: 55°   |                   |   |
|   |                             | 6  | Network  | Network interface | 10Mbps/100Mbps                            |
|   |                             |  |  | Network protocol  | TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P |
|   |                             |  |  | Wireless network  | IEEE802.11b/g/n                           |
| Wireless frequency  | 2.4G                        |  |  |                   |   |
| 7   | Storage                     | Wireless security encryption   | 64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption  |                   |   |
|   |                             | External TF card   | Supports T-Flash cards (up to 256GB)   |                   |   |
|   |                             | Cloud storage  | Support cloud storage, users can purchase according to their needs.                          |                   |   |
| 9   | Physical Indicators         | Alarm detection  | Motion detection, human detection, human framing, human tracking, and area detection         |                   |   |
|   |                             | Rated voltage  | DC5V±5%  |                   |   |
|   |                             | Power consumption  | Power: 1.4W (0.28A) Maximum power: 2.8W (0.56A)  |                   |   |
|   |                             | Operating condition  | Working temperature: -10 ~ 45°C, working humidity <90%                                       |                   |   |
|   |                             | Weight   | Net weight: 158g. Gross weight: 338g   |                   |   |
|   |                             | Camera size  | 76x76x116mm  |                   |   |
|   |                             | Packaging box size   | 90x90x185mm  |                   |   |
| Carton size   | 470x470x395mm, 50PCS/CARTON |  |  |                   |   |