



My safety, My rule!

Model: CS49L

Sorts	Type	Parameters
System	Operating system	Embedded Linux
	Online visitor	Supports 4 visitors at the same time
	Image sensor	1/2.9 inch 1080p progressive scan CMOS sensor
	Minimum illumination	0.5 Lux(Color mode), 0.1 Lux(B&W mode)
	Lens/visual angle	4mm@F2.1/90.9°Diagonal
	Night Vision	IR-CUT with auto-switching, dual light source, 4 white lights, 4 infrared lights, illumination distance 5-10 meters
	Compression standard	H.264 main profile/Motion-JPEG/JPEG
	Data rate	Main stream: 1296p(2304×1296)@25fps Substream: 360p(640×360)@25fps
	Bit rate /maximum frame rate	128~4096kbps/25fps
	Image adjustment	Adjustable brightness and contrast
Audio	Input	Built-in -38dB microphone
	Output	Built-in 8Ω1W speaker
	Sampling frequency/bit width	8KHz/16bit
	Compression standard/bit Rate	G.711/64kbps
Network	Network interface	10Mbps/100Mbps adaptive /RJ45 interface
	Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc.
	Wireless network	IEEE802.11b/g/n; Support AP mode
	Wireless frequency	2.4GHz
	Wireless security encryption	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
Pan&Tilt	Rotation angle	Horizontal 348°/Vertical70°
	Preset position	Supports 16 presets (mobile app only supports 5)
Storage	Storage functions	Supports T-Flash card(max supports 256GB); Cloud Storage;NVR;NAS
Alarm	Alarm detection	Support mobile detection,humanoid detection,human framing,area detection
Physical indicators	Rated voltage	DC 5V±5%
	Power consumption	Rated power: 2.6W (infrared light on)/maximum power: 5.8W (PTZ on)
	Operating condition	Temperature: -10~50°C; Humidity: <90%
	Weight	N.W.: 190 g (Note: in kind prevail)
	Package size	170x150x108mm