


CS995Q-SP

Product Image		Features	
		★F2.0 large aperture, more light intake, clearer night vision.	
		★4 MP Ultra HD	
		★Dual band WiFi, stable connection	
		★Dual core light panel, full-color night vision	
		★ISP image processing technology, preserving true colors	
		★Human detection, real time alerts	
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	O-KAM Pro
2	Collection	CPU	Ingenic
		Memory	512Mb
		Lens	4mm
		Image sensor	1/3 4MP progressive scan CMOS sensor
		Min. Illumination	0.5Lux (color mode), 0.1Lux (b&w mode)
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight compensation
		Night vision	Black and white night vision, full-color night vision
		Viewing angle	Diagonal: 108 °
4	Video	Resolution	4MP 2560x1440/15FPS
		Night vision	Black and white night vision, full-color night vision
		Compression standard	H.264 main profile/Motion-JPEG/JPEG
		IR control	IR-CUT, soft photosensitive control
		Bit rate	128 ~ 4096kbps
		Image adjustment	Brightness, contrast, OSD display
5	Audio	Input	Built-in -38dB microphone
		Output	Built-in 8Ω1W speaker
		Sampling frequency/bit width	8KHz/16bit
		Compression standard/Bit Rate	G711A
6	Pan/Tilt	Rotation angle	Pan: 310° Tilt: 115°
7	Network	Network interface	10Mbps/100Mbps
		Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P
		Wireless network	IEEE802.11b/g/n
		Wireless frequency	2.4G/5G
		Wireless security encryption	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
8	Storage	External TF card	Supports T-Flash cards (up to 256GB)
		Cloud storage	Support cloud storage, users can purchase according to their needs.
9	Alarm	Alarm detection	Motion detection, human detection, human framing, person tracking, and area detection
10	Physical Indicators	Rated voltage	DC5V±12%
		Power consumption	Rated: 2.9W (0.58A); Full function on: 6W (1.2A)
		Operating condition	Working temperature: -10 ~ 45°C, working humidity <90%
		Weight	N.W: 233g G.W: 386g
		Camera size	81x81x132mm
		Packaging box size	90x90x185mm
		Carton size	470x470x395mm, 50PCS/Carton