

H3C Dual-Port 60W Passive Power over Ethernet Adapter



New H3C Technologies Co., Limited

Dual-Port 60W Passive Power over Ethernet Adapter

Overview

ADP060-55V-POE-GL is a dual-Port centralized network remote power adapter, and designed for indoor or outdoor scenarios. The waterproof enclosure is needed for outdoor deployment. Its Voltage input is from 100 to 240VAC. The adapter can connect to network terminal equipment with CAT5e cable, working for 100M/1000M/10G network scenarios.



Features

Item	Specification
Size (W×D×H)	208mm × 85mm × 46mm
Weight	437g
Input Voltage	100V AC∼240V AC; 50/60Hz
Input Current	1.5A Max, at 115Vac, Full load 0.75A Max, at 230Vac, Full load
Input Connector*	IEC320 C14
AC Inrush Current	30A Max. At 115Vac, Cold start.
	60A Max. At 230Vac, Cold start
Output Voltage	55V
Output rated current	1.1A
Total Output Power	60W
Output Connection	Pins 3,6, 4,5(+) Pins 1,2, 7,8 (-)
Item	Specification
Power Efficiency	Level V

OCP, OVP, SCP Protection

-30℃~55℃ Operation: Temperature

Non-operation: -40 °C ~70 °C

Humidity (Non-condensing) 5%~95%

Altitude Up to 5000m

> EN 55032: RE,CE CISPR 32: RE,CE IEC 61000-4-2: ESD IEC 61000-4-3: RS

EMC IEC 61000-4-4: EFT

IEC 61000-4-5: Surge IEC 61000-4-6: CS IEC 61000-4-11: DIPS

Safety Approvals CE,TUV, CCC



New H3C Technologies Co., Limited

Beijing Headquarters

Tower 1, LSH Center, 8 Guangshun South Street, Chaoyang District, Beijing, China Zip: 100102

Hangzhou Headquarters

No.466 Changhe Road, Binjiang District, Hangzhou, Zhejiang, China Zip: 310052

Tel: +86-571-86760000

Disclaimer: Though H3C strives to provide accurate information in this document, we cannot guarantee that details do not contain any technical error or printing error. Therefore, H3C cannot accept responsibility for any inaccuracy in this document. H3C reserves the right for the modification of the contents herein without prior notification

http://www.h3c.com

^{*} Note: AC power cord will be configured with the adapter according to the country or areas