


Key Features

- SuperClear® IPS panel
- Full HD 1080p resolution
- 100Hz Variable Refresh Rate delivers fluid visuals
- 1ms (MPRT) response time for precision
- Built-in Low Blue Light Screen for comfortable viewing



Product **Description**

The ViewSonic VA2432-H-W is a 24" 1080p IPS monitor featuring HDMI and VGA inputs for business and home use. The optimal screen performance and comfortable viewing without tearing or stuttering is delivered through Variable Refresh Rate, eye-care technology, and various ViewMode presets. Simply expand your workspace and experience truly seamless, ergonomic multitasking on just one screen with a VESA-compatible mount at a low power consumption.



Visit Us

www.viewsonic.com

Display Size (in.):	24		Key 1 (favorite), Key 2, Key
Viewable Area (in.):	23.8	Physical Controls:	3, Key 4, Key 5 (power)
Panel Type:	IPS Technology		Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Resolution:	1920 x 1080	On Screen Display:	
Resolution Type:	FHD (Full HD)	OPERATING CONDITIONS	0005 / 40405 (000 / 4000)
Static Contrast Ratio:	1,000:1 (typ)	Temperature:	32°F to 104°F (0°C to 40°C)
Dynamic Contrast Ratio:	50M:1	Humidity (non-condensing):	20% to 90%
Light Source:	LED	WALL MOUNT	75 75
Brightness:	250 cd/m² (typ)	VESA Compatible:	75 x 75 mm
Colors:	16.7M	INPUT SIGNAL	DOD A 1 04 001/11
Color Space Support:	8 bit (6 bit + FRC)	Frequency Horizontal:	RGB Analog: 24 ~ 86KHz, HDMI (v1.4): 30 ~ 115KHz
Aspect Ratio:	16:9	Frequency Vertical:	RGB Analog: 48 ~ 75Hz,
Response Time (MPRT):	1ms	Frequency Vertical:	HDMI (v1.4): 48 ~ 100Hz
Viewing Angles:	178º horizontal, 178º vertical	VIDEO INPUT	
Backlight Life (Hours):	30000 Hrs (Min)	Digital Sync:	TMDS - HDMI (v1.4)
Curvature:	Flat	Analog Sync:	Separate - RGB Analog
Refresh Rate (Hz):	100	ERGONOMICS	
Variable Refresh Rate	Yes	Tilt (Forward/Back):	-3° / 20°
Technology:		WEIGHT (IMPERIAL)	
Low Blue Light:	Hardware and software solution	Net (lbs):	6
Flicker-Free:	Yes	Net Without Stand (lbs):	5.3
Color Gamut:	NTSC: 75% size (Typ) sRGB: 105% size / 99% coverage (Typ)	Gross (lbs):	8.2
		WEIGHT (METRIC)	
Pixel Size:	0.275 mm (H) x 0.275 mm (V)	Net (kg):	2.7
Surface Treatment:	Anti-Glare, Hard Coating (3H)	Net Without Stand (kg):	2.4
COMPATIBILITY	Anti-Glare, Hard Coating (SH)	Gross (kg):	3.7
PC Resolution (max):	1920x1080	DIMENSIONS (IMPERIAL) (W	XHXD)
,	1920x1080	Packaging (in.):	23.6 x 15.6 x 4.4
Mac® Resolution (max):		Physical (in.):	21.3 x 16 x 7.3
PC Operating System:	Windows 10/11 certified; macOS tested	Physical Without Stand (in.):	21.3 x 12.7 x 1.4
Mac® Resolution (min):	1920x1080	DIMENSIONS (METRIC) (WXHXD)	
CONNECTOR		Packaging (mm):	600 x 395 x 112
VGA:	1	Physical (mm):	540 x 406 x 185
3.5mm Audio Out:	1	Physical Without Stand (mm):	540 x 322 x 36
HDMI 1.4:	1	GENERAL	
Power in:	DC Socket (Center Positive)	Regulations:	CE, CE EMC, CB, RoHS, ErF REACH, WEEE, EAC, UKrSEPRO, BSMI, RCM,
POWER			
Eco Mode (Conserve):	15W		GEMS, KC, K-MEPS, BIS
Eco Mode (optimized):	18W	PACKAGE CONTENTS:	VA2432-H-W x1, HDMI Cable (v1.4; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x1 or 2 (by country)
Consumption (typical):	22W		
Consumption (max):	25W		
Voltage:	AC 100-240V	Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Stand-by:	0.3W		
•		Warranty:	*Warranty offered may differ
Power Supply:	External Power Adaptor		from market to market
ADDITIONAL HARDWARE	,		
Kensington Lock Slot:	1		