



LCD DISPLAY

# VX2758A-2K-PRO-3

## Key Features

- Conquer every challenge with the silky-smooth 240Hz refresh rate
- Obliterate motion blur with the rapid 1ms (MPRT) response time
- Conquer stuttering and tearing with AMD FreeSync™ Premium for smooth action
- Dual HDMI and DisplayPort inputs for flexible connectivity



## Product Description

Dive into the heart of gaming with the ViewSonic GAMING VX2758A-2K-PRO-3 monitor. Featuring a SuperClear IPS anti-glare panel and HDR10 support, this monitor renders gaming worlds in stunning 2K QHD resolution—where details pop off the screen and vivid, consistent colors dazzle from wide viewing angles. Sharpen your competitive edge and gain the upper hand in fast-paced gaming sessions with the heart-pounding 240Hz refresh rate, ensuring animations are smooth and remarkably fluid at those moments where every frame can swing the outcome from defeat to victory. Enhanced with AMD FreeSync™ Premium technology, the monitor effectively eliminates screen tearing and reduces stuttering, allowing you to stay fully immersed in seamless, high-octane action. Taking the immersion further, the lightning-fast 1ms (MPRT) response time ensures that on-screen actions are as instantaneous as your reflexes, enabling you to dominate the battlefield with near lag-free, pinpoint accuracy. Beyond the VX2758A-2K-PRO-3 gaming monitor's powerful performance, it comes equipped with versatile connectivity options, including dual HDMI 2.1 inputs and DisplayPort. This allows for seamless switching between multiple connected PCs, game consoles, and other devices, making it not only a powerhouse for gaming but also versatile enough to excel in cinematic entertainment and boundless creative projects.



1. Display Port \*1
2. HDMI 2.1 \*2
3. OSD Joystick
4. AC In
5. VESA Wall Mount Compatible (100 x 100mm)

**DISPLAY**

Display Size (in.):	27
Viewable Area (in.):	27
Panel Type:	IPS Technology
Resolution:	2560 x 1440
Resolution Type:	QHD (Quad HD)
Static Contrast Ratio:	1,000:1 (typ)
Dynamic Contrast Ratio:	80M:1
High Dynamic Range:	HDR10
Light Source:	LED
Brightness:	300 cd/m <sup>2</sup> (typ)
Colors:	1.07B
Color Space Support:	10 bit (8 bit + FRC)
Aspect Ratio:	16:9
Response Time (MPRT):	1ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	240
Variable Refresh Rate Technology:	FreeSync for HDMI; FreeSync Premium for DP
Low Blue Light:	Software solution
Flicker-Free:	Yes
Color Gamut:	NTSC: 92% size (Typ) sRGB: 130% size / 99% coverage (Typ)
Pixel Size:	0.233 mm (H) x 0.233 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

**COMPATIBILITY**

PC Resolution (max):	2560x1440
Mac® Resolution (max):	2560x1440
PC Operating System:	Windows 10/11 certified; macOS tested
Mac® Resolution (min):	2560x1440

**CONNECTOR**

3.5mm Audio Out:	1
HDMI 2.1:	2
DisplayPort:	1
Power in:	3-pin Socket (IEC C14 / CEE22)

**POWER**

Eco Mode (Conserve):	19W
Eco Mode (optimized):	24W
Consumption (typical):	28W
Consumption (max):	30W
Voltage:	AC 100-240V
Stand-by:	0.5W
Power Supply:	Internal Power Supply

**ADDITIONAL HARDWARE**

Kensington Lock Slot:	1
-----------------------	---

**CONTROLS**

Physical Controls:	Up, Right, Down, Left, Power
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

**OPERATING CONDITIONS**

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

**WALL MOUNT**

VESA Compatible:	100 x 100 mm
------------------	--------------

**INPUT SIGNAL**

Frequency Horizontal:	HDMI (v2.1): 24 ~ 222KHz, DisplayPort (v1.4): 24 ~ 255KHz
Frequency Vertical:	HDMI (v2.1): 48 ~ 144Hz, DisplayPort (v1.4): 48 ~ 240Hz

**VIDEO INPUT**

Digital Sync:	TMDS compatible - HDMI (v2.1), PCI-E - DisplayPort (v1.4)
---------------	---

**ERGONOMICS**

Tilt (Forward/Back):	-5° / 20°
----------------------	-----------

**WEIGHT (IMPERIAL)**

Net (lbs):	10.8
Net Without Stand (lbs):	9.8
Gross (lbs):	14

**WEIGHT (METRIC)**

Net (kg):	4.9
Net Without Stand (kg):	4.5
Gross (kg):	6.4

**DIMENSIONS (IMPERIAL) (WXHxD)**

Packaging (in.):	27.8 x 18.5 x 5
Physical (in.):	24.18 x 17.85 x 7.1
Physical Without Stand (in.):	24.18 x 14.4 x 1.85

**DIMENSIONS (METRIC) (WXHxD)**

Packaging (mm):	706 x 471 x 128
Physical (mm):	614.1 x 453.35 x 180.26
Physical Without Stand (mm):	614.1 x 365.65 x 47.05

**GENERAL**

Regulations:	CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, BSMI, RCM, VCCI, PSE, BIS
PACKAGE CONTENTS:	VX2758A-2K-PRO-3 x1, 3-pin Plug (IEC C13 / CEE22) x1, DisplayPort Cable (v1.4; Male-Male) x1, Quick Start Guide x1
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Warranty:	*Warranty offered may differ from market to market