

ViewSonic® LCD DISPLAY VX2762U-4K

Key Features

- SuperClear® IPS panel ensures wide viewing angles and vibrant colors
- 4K UHD resolution delivers crystal-clear details
- HDR10 offers stellar contrast and color accuracy
- Integrated Blue Light filter and flicker-free technology ensure comfortable viewing
- Enjoy hassle-free connectivity with HDMI and DisplayPort inputs



Product Description

The VX2762U-4K monitor displays every detail with precision and clarity, whether you're working, creating, or playing. Its SuperClear® IPS panel delivers impeccable color accuracy and wide viewing angles, while the 4K UHD resolution provides breathtakingly sharp visuals that bring images to life. With HDR10 support for enhanced contrast and brightness; Eye Protech flicker-free and blue light filter technology to reduce eye strain; and versatile HDMI and DisplayPort inputs, this monitor excels for work and entertainment.

Visit Us www.viewsonic.com

DISPLAY

Display Size (in.):	27
Viewable Area (in.):	27
Panel Type:	IPS Technology
Resolution:	3840 x 2160
Resolution Type:	UHD (Ultra HD)
Static Contrast Ratio:	1,000:1 (typ)
Dynamic Contrast Ratio:	50M:1
High Dynamic Range:	HDR10
Light Source:	LED
Brightness:	250 cd/m ² (typ)
Colors:	1.07B
Color Space Support:	10 bit (8 bit + FRC)
Aspect Ratio:	16:9
Response Time (GTG w/OD):	3.8ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	60
Low Blue Light:	Software solution
Flicker-Free:	Yes
Color Gamut:	NTSC: 72% size (Typ) sRGB: 104% size (Typ)
Pixel Size:	0.155 mm (H) x 0.155 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

COMPATIBILITY

PC Resolution (max):	3840x2160
Mac® Resolution (max):	3840x2160
PC Operating System:	Windows 10/11 certified; macOS tested
Mac® Resolution (min):	3840x2160

CONNECTOR

USB 3.2 Type A Down Stream:	2
USB 3.2 Type B Up Stream:	1
USB 3.2 Type C DisplayPort Alt mode only :	1 (65W power charger)
3.5mm Audio Out:	1
HDMI 2.0 (with HDCP 2.2):	2
DisplayPort:	1
Power in:	3-pin Socket (IEC C14 / CEE22)

AUDIO

Internal Speakers:	2.5Watts x2
--------------------	-------------

POWER

Eco Mode (Conserve):	23W
Eco Mode (optimized):	30W
Consumption (typical):	38W
Consumption (max):	45W
Voltage:	AC 100-240V
Stand-by:	0.5W
Power Supply:	Internal Power Supply

ADDITIONAL HARDWARE

Kensington Lock Slot:	1
Cable Organization:	Yes

CONTROLS

Physical Controls:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

OPERATING CONDITIONS

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

WALL MOUNT

VESA Compatible:	100 x 100 mm
------------------	--------------

INPUT SIGNAL

Frequency Horizontal:	HDMI (v2.0): 15 ~ 240KHz, DisplayPort (v1.4): 31 ~ 160KHz, Type C: 31 ~ 160KHz
Frequency Vertical:	HDMI (v2.0): 29 ~ 60Hz, DisplayPort (v1.4): 48 ~ 60Hz, Type C: 48 ~ 60Hz

VIDEO INPUT

Digital Sync:	TMDS - HDMI (v2.0), PCI-E - DisplayPort (v1.4), Micro-Packet - Type C
---------------	---

ERGONOMICS

Height Adjust (mm):	150
Swivel:	90°
Tilt (Forward/Back):	-3.5° / 20°
Pivot (Right/Left):	90° / 90°

WEIGHT (IMPERIAL)

Net (lbs):	14.3
Net Without Stand (lbs):	9.7
Gross (lbs):	17.9

WEIGHT (METRIC)

Net (kg):	6.5
Net Without Stand (kg):	4.4
Gross (kg):	8.1

DIMENSIONS (IMPERIAL) (WXHXD)

Packaging (in.):	30.1 x 17.8 x 5
Physical (in.):	24.2 x 15.51~21.43 x 8.4
Physical Without Stand (in.):	24.2 x 14.4 x 2

DIMENSIONS (METRIC) (WXHXD)

Packaging (mm):	764 x 452 x 126
Physical (mm):	614 x 394~544.2 x 214
Physical Without Stand (mm):	614 x 366 x 51

GENERAL

Regulations:	RoHS, WEEE, BIS
PACKAGE CONTENTS:	VX2762U-4K x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v2.0; Male-Male) x1, USB Type-C Cable (Male-Male) x1, USB A/B Cable (v3.2; Male-Male) x1, Quick Start Guide x1
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Warranty:	*Warranty offered may differ from market to market