ViewSonic VX3219-PC-MHD 32" 240Hz Curved Gaming Monitor - Datasheet - ViewSonic Global

ViewSonic Mile VX3219-PC-MHD

Key Features

- 240Hz refresh rate for smooth gameplay
- 1ms (MPRT) response time for precision
- 1500R Curved screen for immersive visuals
- AMD FreeSync™ Premium prevents screen tearing
- Full HD resolution for rich detail



Product **Description**

Upgrade your PC experience with the 32" VX3219-PC-MHD. The large display features a 1500R curve for truly immersive gameplay and the ultra-responsive 240Hz display provides pro-level refresh rates, so you can stay ahead of the competition and enjoy ultra-smooth gaming no matter how intense the action gets. A clean design, with 3-side borderless display and sleek dimensions create a product that delivers all you need. Adaptive[™] Sync technology virtually eliminates screen tearing and stuttering for a fluid gaming experience. And the 1ms MPRT response time enables you to react in-game with complete precision, removing ghosting and motion blur. VX3219-PC-MHD is also equipped with ViewSonic's exclusive ViewMode[™] presets, which offer optimized screen performance for a variety of needs, such gaming, editing, or watching movies. In addition, a DisplayPort and HDMI inputs offer flexible connectivity for gaming and entertainment.

Visit Us www.viewsonic.com

ViewSonic VX3219-PC-MHD 32" 240Hz Curved Gaming Monitor - Datasheet - ViewSonic Global

DISPLAY		CONTROLS	
Display Size (in.):	32	Physical Controls:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)
Viewable Area (in.):	31.5	On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Panel Type:	VA Technology		
Resolution:	1920 x 1080		
Resolution Type:	FHD (Full HD)	OPERATING CONDITIONS	
Static Contrast Ratio:	3,000:1 (typ)	Temperature:	32°F to 104°F (0°C to 40°C
Dynamic Contrast Ratio:	80M:1	Humidity (non-condensing):	20% to 90%
High Dynamic Range:	HDR10	WALL MOUNT	
Light Source:	LED	VESA Compatible:	100 x 100 mm
Brightness:	300 cd/m² (typ)	INPUT SIGNAL	
Colors:	16.7M	Frequency Horizontal:	HDMI (v2.0): 31.469 ~ 291.309KHz, DisplayPort (v1.4): 31.469 ~ 219.309KH
Color Space Support:	8 bit (6 bit + FRC)		
Aspect Ratio:	16:9	Frequency Vertical:	HDMI (v2.0): 48 ~ 240Hz, DisplayPort (v1.4): 48 ~ 240Hz
Response Time (MPRT):	1ms		
Viewing Angles:	178º horizontal, 178º vertical	VIDEO INPUT	
Backlight Life (Hours):	30000 Hrs (Min)	Digital Sync:	TMDS - HDMI (v2.0), PCI-E DisplayPort (v1.4)
Curvature:	1500R	ERGONOMICS	,,
Refresh Rate (Hz):	240	Tilt (Forward/Back):	-5° / 20°
Variable Refresh Rate	FreeSync Premium	WEIGHT (IMPERIAL)	
Technology:	-	Net (lbs):	10.4
Low Blue Light:	Software solution	Net Without Stand (lbs):	9.3
Flicker-Free:	Yes	Gross (lbs):	15.4
Color Gamut:	NTSC: 72% size (Typ) sRGB: 103% size (Typ)	WEIGHT (METRIC)	
Pixel Size:	0.364 mm (H) x 0.364 mm (V)	Net (kg):	4.7
Surface Treatment:	Anti-Glare, Hard Coating (3H)	Net Without Stand (kg):	4.2
COMPATIBILITY		Gross (kg):	7
PC Resolution (max):	1920x1080	DIMENSIONS (IMPERIAL) (W	XHXD)
Mac® Resolution (max):	1920x1080	Packaging (in.):	38.2 x 20.6 x 6.7
PC Operating System:	Windows 11 certified; macOS tested	Physical (in.):	27.9 x 20.2 x 9
Mac® Resolution (min):	1920x1080	Physical Without Stand (in.):	27.9 x 16.5 x 3.7
	192021000	DIMENSIONS (METRIC) (WXH	IXD)
3.5mm Audio Out:	1	Packaging (mm):	970 x 523 x 170
HDMI 2.0:	2	Physical (mm):	709 x 513 x 228
DisplayPort:	1	Physical Without Stand (mm):	709 x 419 x 93
Power in:		GENERAL	
Power III.	DC Socket (Center Positive)		cTUVus, FCC-B, ICES003,
AUDIO	2Watts x2	Regulations:	CEC, NOM, Mexico Energy CE, CE EMC, CB, RoHS, E
Internal Speakers:	2Watts x2	Regulations:	CEC, NOM, Mexico Energy, CE, CE EMC, CB, RoHS, E REACH, WEEE, EAC, UkrSEPRO, BSMI, RCM,
Internal Speakers: POWER		Regulations:	CEC, NÓM, Mexico Energy, CE, CE EMC, CB, RoHS, E REACH, WEEE, EAC, UkrSEPRO, BSMI, RCM, GEMS, BIS
Internal Speakers: POWER Eco Mode (Conserve):	25W	Regulations:	CEC, NÓM, Mexico Energy, CE, CE EMC, CB, RoHS, E REACH, WEEE, EAC, UkrSEPRO, BSMI, RCM, GEMS, BIS VX3219-PC-MHD x1, 3-pin Plug (IEC C13 / CEE22) x1
Internal Speakers: POWER Eco Mode (Conserve): Eco Mode (optimized):	25W 31W	Regulations: PACKAGE CONTENTS:	CEC, NÓM, Mexico Energy, CE, CE EMC, CB, RoHS, E REACH, WEEE, EAC, UkrSEPRO, BSMI, RCM, GEMS, BIS VX3219-PC-MHD x1, 3-pin Plug (IEC C13 / CEE22) x1 DisplayPort Cable (v1.2; Male-Male) x1, AC/DC
Internal Speakers: POWER Eco Mode (Conserve): Eco Mode (optimized): Consumption (typical):	25W 31W 37W		CEC, NOM, Mexico Energy, CE, CE EMC, CB, RoHS, E REACH, WEEE, EAC, UkrSEPRO, BSMI, RCM, GEMS, BIS VX3219-PC-MHD x1, 3-pin Plug (IEC C13 / CEE22) x1 DisplayPort Cable (v1.2;
Internal Speakers: POWER Eco Mode (Conserve): Eco Mode (optimized): Consumption (typical): Consumption (max):	25W 31W 37W 40W		CEC, NOM, Mexico Energy, CE, CE EMC, CB, RoHS, E REACH, WEEE, EAC, UkrSEPRO, BSMI, RCM, GEMS, BIS VX3219-PC-MHD x1, 3-pin Plug (IEC C13 / CEE22) x1 DisplayPort Cable (v1.2; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1
Internal Speakers: POWER Eco Mode (Conserve): Eco Mode (optimized): Consumption (typical): Consumption (max): Voltage:	25W 31W 37W 40W AC 100-240V		CEC, NÓM, Mexico Energy, CE, CE EMC, CB, RoHS, E REACH, WEEE, EAC, UkrSEPRO, BSMI, RCM, GEMS, BIS VX3219-PC-MHD x1, 3-pin Plug (IEC C13 / CEE22) x1 DisplayPort Cable (v1.2; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1 Please dispose of in accordance with local, state
Internal Speakers: POWER Eco Mode (Conserve): Eco Mode (optimized): Consumption (typical): Consumption (max): Voltage: Stand-by:	25W 31W 37W 40W AC 100-240V 0.5W	PACKAGE CONTENTS:	CEC, NOM, Mexico Energy, CE, CE EMC, CB, RoHS, E REACH, WEEE, EAC, UkrSEPRO, BSMI, RCM, GEMS, BIS VX3219-PC-MHD x1, 3-pin Plug (IEC C13 / CEE22) x1 DisplayPort Cable (v1.2; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1 Please dispose of in accordance with local, state or federal laws.
Internal Speakers: POWER Eco Mode (Conserve): Eco Mode (optimized): Consumption (typical): Consumption (max): Voltage:	25W 31W 37W 40W AC 100-240V	PACKAGE CONTENTS:	CEC, NOM, Mexico Energy, CE, CE EMC, CB, RoHS, E REACH, WEEE, EAC, UkrSEPRO, BSMI, RCM, GEMS, BIS VX3219-PC-MHD x1, 3-pin Plug (IEC C13 / CEE22) x1 DisplayPort Cable (v1.2; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1 Please dispose of in accordance with local, state