

# ASUS VT229H

## 10-point Multi-touch Monitor



### Key Features



Low Blue Light & Flicker Free



IPS technology panel is optimized for the finest image and color quality with 178° wide-viewing-angle




10-point Touch

Capacitive 10-point multi-touch capability plus an over 100Hz reporting rate ensures smooth and intuitive touch Experience



With the best compatibility and reliability, VT229 ensures outstanding accuracy and effortless control in Windows 10.



Frameless Design

3-side frameless panel design gives you edge-to-edge visuals.



Flicker-free

ASUS Flicker-Free Technology clears out the distracting flicker, and brings viewing comfort.



Ultra-low Blue Light

Four levels of Blue Light Filter help users effectively reduce harmful blue light from the screen by tasks.



Extensive connectivity with HDMI, D-sub, Audio in



Stereo Speaker

Built-in 1.5W stereo speakers for audio experience



Wall Mountable

Compatible with VESA Wall Mount Standard (100 x 100 mm).



# Specification

Display	Panel Size(diagonal)	21.5"(54.6cm) Wide Screen (16:9)
	Display Viewing Area(HxV)	476.64 x 268.11mm
	Panel Type/ Backlight	IPS, WLED backlight
	Display Surface	Glare, 7H hardness rating
	Color Saturation	72% NTSC
	True Resolution	1920 x 1080
	Pixel Pitch	0.2482mm
	Brightness (Max.)	250cd/m <sup>2</sup>
	Contrast Ratio (Max.)	1000:1
	ASUS Smart Contrast Ratio(ASCR)	100,000,000:1
	Viewing Angle (CR ≥ 10)	178°(H)/178°(V)
	Display Colors	16.7 million
	Response Time	5ms (GTG)
	Touch Screen	Yes / Capacitive 10-point multi-touch
	Frameless design	Yes, 3-side frameless
Flicker-free	Yes	
Video Features	SplendidPlus™ Video Intelligence Tech.	Yes
	Skin-Tone Selection	3 modes
	Color Temperature Selection	4 modes (Cool/Normal/Warm/User)
	HDCP	Yes
	QuickFit	Yes (Alignment Grid / Photo)
	Blue Light Filter	Yes
Audio Features	Stereo Speaker	1.5W x 2 stereo, RMS
Input/ Output		HDMI, D-Sub, Audio-in, USB2.0 port (for touch signal)
Signal Frequency	Analog Signal Frequency	30~83 KHz(H)/ 50~75 Hz(V)
	Digital Signal Frequency	30~83 KHz(H)/ 50~75 Hz(V)
Power	Power Consumption	< 21.9W*
	Power Saving/ Off Mode	<0.5W
	Voltage	100~240V, 50 / 60 Hz
Mechanical Design	Chassis Colors	Black
	Tilt(angle)	+20° ~ -5°
	VESA Wall Mounting	100x100mm
Security	Kensington lock	Yes
Dimension	Phys. Dimension (WxHxD)	491.5 x 367.7 x 204.4 mm (with stand) 491.5 x 300.1 x 51.9 mm(without stand)
	Box Dimension (WxHxD)	558 x 430 x 137 mm
Weight	3.83Kg(Net); 3.18kg(Net Weight without Stand ) 6.13 Kg (Gross)	
Accessories	Power Cord(1.5m), USB cable(for touch signal, 1.5m), HDMI cable (1.5m)(optional), VGA cable(1.5m)(optional), Audio cable(1.5m), Warranty Card, Quick start guide	
Compliance Standards	Energy Star®, UL/cUL, CB, CE, ErP, FCC, CCC,RCM, BSMI, VCCI, RoHS, J-MOSS, MEPS, WEEE, PSE, ISO 9241-307, Windows 7/ 8.1/10 WHQL, CEL, KC, KCC, e-Standby, TÜV flicker free, TÜV low blue light	

\*measuring a screen brightness of 200 nits without audio/ USB connection

\*\*All specifications are subject to change without notice.