


BG67D Dual Lens low-power 4G waterproof dome camera

Product Image		Product features	
		★2K UHD wireless connection	
		★Remote active wake-up, two-way voice intercom	
		★400ms quick start	
		★Intelligent detection of human movement, intelligent alarm push	
		★Dual lens, free choice of far and near focus, HD image is close to your eyes.	
		★Ultra-low power system optimization	
		★Free cloud storage to save alarm videos	
		★Support external connection of 5W-15W voltage stabilizer free solar panel, continuous power supply, and the device will not powered off	
★Dual light source, full color day and night			
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
2	Collection	CPU	T31
		No. of Lens	Dual Lens
		Lens	4mm+12mm Long focus lens+short focus lens, IRCUT integrated
		Image sensor	1/2.9 CMOS sensor
		Minimum illumination	0.01Lux
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight
		Night Vision	4 IR lights+4 white lights, Dual light source, 20MIL,850nm wavelength
		Viewing angle	100°/30°
3	Video	Resolution	2304×1296P/15fps/3MP
		Zoom	Dual lens stepless 5x hybrid zoom
		Night Vision	Full color night vision/black and white night vision/intelligent night vision
		Compression standard	H.264 /MJPEF/JPEG
		IR control	When the IR night vision function is enabled, IR and ICR are automatically detected; when the IR night vision function is disabled, IR is off and ICR is fixed in the day vision mode.
		Bit rate	CBR/VBR two rate control modes, and the output rate range is 128 ~ 4096kbps
4	Audio	Image adjustment	Flip up and down, OSD display
		Input	Built-in-38dB microphone
		Output	Built-in 8Ω1W speaker
		Sampling frequency/bit width	8KHz/16bit
		Compression standard/Bit Rate	G711A
5	AI	Humanoid detection	Humanoid detection, filtering invalid video content
		Object tracking	/
		Area detection	Free daub, only monitoring the areas concerned by users
		Smart notification sound	Different devices push different sounds, so that you can know exactly which device is
		Intelligent alarm sound	Set different equipment alarm sounds according to different scenarios
6	Network	Wireless connection	Scan the device QR code to add/scan the APP QR code
		Domestic Cat1	FDD:B1/B3/B5/B8 TDD:B34/B38/B39/B40/B41
		Overseas Cat4	Europe/USA version LTE-FDD: B1/B3/B7/B8/B20 LTE-TDD: B40/B41
7	Key/interface	USB	Micro usb/Charging port
		Key1	Toggle switch/left and right toggle switch mode
		Reset key	1 reset key/long press to restore factory settings
8	Storage	External TF card	Support TF card (up to 256GB)
		Cloud storage	Free loop cloud storage
9	Alarm	Alarm detection	Motion detection/PIR human detection/humanoid detection, adjustable distance by gear, detection distance up to 15M
10	Physical Indicators	Rated voltage	DC5V±5%
		Operating condition	Temperature: -10 ~ 50°C; Humidity: < 90%
		Weight	Gross weight: 1070g (Note: in kind prevail)
		Size	Camera: 233 * 109 * 133mm, Color box: 205 * 181 * 147mm, Outer packaging box: 560 * 425 * 470mm, 18PCS/box
		Packing list	Camera * 1, screw package, MICRO USB * 1, manual * 1, (solar panel * 1, solar panel bracket * 1 optional)