


C662DR

Product Image		Features	
		★ Dual lens dual view leaves no blind spots	
		★ Dual-core light panel, color night vision	
		★ ISP image processing technology, preserving true colors	
		★ Human detection, real time alerts	
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	O-KAM Pro
2	Collection	CPU	Ingenic
		Memory	512Mb
		Lens	4mm
		Image sensor	1/4.5-inch high-quality 1-megapixel CMOS image sensor
		Min. Illumination	0.5Lux (color mode), 0.1Lux (b&w mode)
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight compensation
		Night vision	Black and white night vision, full-color night vision
		Viewing angle	58°
3	Video	Resolution	720P 1280X720/15FPS/1MP
		Night vision	Black and white night vision, full-color night vision
		Compression standard	H.264 main profile/Motion-JPEG/JPEG
		IR control	IR-CUT, soft photosensitive control
		Bit rate	128 ~ 4096kbps
		Image adjustment	Brightness, contrast, OSD display
4	Audio	Input	Built-in -38dB microphone
		Output	Built-in 8Ω1W speaker
		Sampling frequency/bit width	8KHz/16bit
		Compression standard/Bit Rate	G711A
5	Pan/Tilt	Rotation angle	Horizontal: 350° Vertical: 90°
6	Network	Network interface	10Mbps/100Mbps
		Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P
		Wireless network	IEEE802.11b/g/n
		Wireless frequency	2.4G
		Wireless security encryption	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
7	Storage	External TF card	Supports T-Flash cards (up to 256GB)
		Cloud storage	Support cloud storage, users can purchase according to their needs.
8	Alarm	Alarm detection	Motion detection, human detection, human framing, siren alarm, and area detection
9	Physical Indicators	Rated voltage	DC12V±5%
		Power consumption	Power: 4.92W (0.41A), maximum power: 9.96W (0.83A)
		Operating condition	Working temperature: -10~55 °C, working humidity<90%
		Weight	Net weight: 412g, gross weight: 712g
		Camera size	136x125x178mm
		Packaging box size	205x160x140mm
		Carton size	580x425x345mm,16PCS/CARTON