



Low Power Battery Bullet Camera -- CB11

| Product picture | | Product characteristics | |
|-----------------|---------------------|---|---|
| Serial number | Category | Type | Parameters |
| 1 | System | Operating system | Linux |
| | | Online visitors | Support 4 visitors online at the same time |
| 2 | Collection | Processor | T31ZL 1.5GHZ |
| | | Image sensor | GC2063, 2MP, 1/2.9 CMOS (pixel optional, PCB compatible) |
| | | Minimum illumination | 0.8Lux/F1.4 (Color mode), 0.3Lux/F1.4 (B&W mode) |
| | | Lens | Standard lens 4mm , 1G3P , IR-CUT integrated |
| | | Sensor performance | Support Automatic white balance, Automatic gain control, Automatic backlight compensation |
| | Viewing angle | D110 ° diagonal | |
| 3 | Video | Night vision | Dual light sources, Full color day & night; 2 pcs IR LED lights+2 pcs LED lights |
| | | Compression standard | H.264 /MJPEF/JPEG |
| | | Multi code stream | 1080p / 15fps, 360p, JPEG capture |
| | | IR control | IR turned on-- the Night vision ON; IR, ICR automatic detection; IR turned off-- the Night vision function disabled/ IR always OFF, ICR is fixed in the Day vision mode |
| | | Bit rate | CBR / VBR two rate control modes, and the output rate range is 128 ~ 4096kbps |
| | | Image adjustment | Brightness, contrast, vertical, horizontal adjustable, OSD display |
| 4 | Audio | Input | Built-in - 38dB microphone |
| | | Output | Built-in 8 Ω 2W speaker |
| | | Sampling frequency / Bit width | 8KHz/ 16bit |
| | | Compression standard / Bit rate | G711A |
| 5 | Network | Network protocol | TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,P2P , IPV4 etc |
| | | Wireless network | IEEE802.11b/g/n |
| | | Wireless frequency | 2.4~2.4835GHz |
| | | Wireless security encryption | 64/ 128-bit WEP/WPA -PSK/WPA2 -PSK data encryption |
| | | Wireless connection | AP hotspot network configuration, QR code network configuration |
| 6 | Key | Key 1 | Power ON/OFF |
| | | Reset Key | Long Press to restore the factory settings |
| 7 | Storage | Storage function | Support T-Flash card (up to 256GB) |
| 8 | Alarm | Alarm detection | Support PIR human detection; Detection distance: 8m |
| 9 | Physical indicators | Rated voltage | DC5V±5% |
| | | Power supply | Comes with 12000mAh battery power supply, supports external 5V solar panels |
| | | Power consumption | Sleep current 500uA, Working current: 390mA |
| | | Work environment | Working temperature: - 10 ~ 55 °C, Working humidity < 90% |
| | | Weight | Gross weight: TBD (Note: in kind prevail) |
| | | Size | TBD |
| | Packing list | Camera * 1, Bracket * 1, MICRO USB* 1, Manual * 1,(Solar panel*1, Solar panel bracket*1 optional) | |