Product image  Product features  # 8 AM Pillina is 10  # Black light full color, presenting color image even with no supplement light  # 15.6 targe aperture, clearer night vision  # 65P image processing a full color image in 24 hours  # 65P image processing a full color image in 24 hours  # 65P image processing technology, presenting a full color image in 24 hours  # 65P image processing technology, presenting a full color image in 24 hours  # 65P image processing technology, presenting a full color image in 24 hours  # 65P image processing technology, presenting a full color image in 24 hours  # 65P image processing technology, presenting a full color image in 24 hours  # 65P image processing technology, presenting a full color image in 24 hours  # 65P image processing technology, presenting a full color image in 25P image i					
Product Image  Product Features  # 3 MP Ultra IID  # Black light fail color, presenting color image even with no supplement light  # 15 lives aperture, clearer night vision  # Soft light design, presenting a full color image in 24 hours  # 15 lives processing technology, proserving true colors  # Human detection, real time alerts  # Remote access, view the manitoring areas anytime and anywhere  1 System  Operating system  Unix  Support automatic white balance, automatic gain control and automatic backlight  sensor performance  Support automatic white balance, automatic gain control and automatic backlight  sensor performance  Support automatic white balance, automatic gain control and automatic backlight  sensor performance  Support automatic virile operating system  Unix  Unix  Operating system  Unix  Operatin				CS611_UV	
## S MP Ultra HD ## Black light full color, presenting color image even with no supplement light ## FLG large aperture, clearer night vision ## Soft light design, presenting a full color image in 24 hours ## Soft light design, presenting a full color image in 24 hours ## Human detection, real time alors ## Remote access, year the monitoring areas anytime and anywhere ## Remote access, year the monitoring areas anytime and anywhere ## Departure system Unius    Operating system				C3011-0 V	
# Black light full color, presenting color image even with no supplement light #F1.6 large aperture, clearer night vision #Soft light design, presenting a full color image in 24 hours #ISP image processing technology, presenting a full color image in 24 hours #ISP image processing technology, presenting a reas anytime and anywhere ##I with man detection, real time alerts ##I with man detection, real time alerts ##I with man detection are alternated in the same time Online vistor Online vistor Online vistor APP O-KAM pro CPU Signature SKC313 Herno Himper SKC313 Herno Himper SKC313 Herno Himper SKC313 Himper SKC3	Product Image			Product features	
# F1.6 large aperture, clearer night vision # Soft light design, presenting a full color image in 24 hours # Soft light design, presenting a full color image in 24 hours # Soft light design, presenting a full color image in 24 hours # Soft light design, presenting a full color image in 24 hours # Soft light design, presenting a full color image in 24 hours # Human detection, real time alerts # Remote access, view the monitoring areas anytime and anywhere  Parameters  Online voitor Supports 4 visitors at the same time Online voitor Supports 4 visitors at the same time Online voitor Supports 4 visitors at the same time Online voitor Supports 4 visitors at the same time  Online voitor Supports 4 visitors at the same time  Online voitor Supports 4 visitors at the same time  Online voitor Supports 4 visitors at the same time Online voitor Supports 4 visitors at the same time Online voitor Supports 4 visitors at the same time Online voitor Supports 4 visitors at the same time Online voitor Supports 4 visitors at the same time Online voitor Supports 4 visitors at the same time Online voitor Supports 4 visitors at the same time Online voitor Supports 4 visitors at the same time Online voitor Supports 4 visitors at the same time Online voitor Supports 4 visitors at the same time Online voitor Supports 4 visitors at the same time Online voitor Supports 4 visitors at the same time Online voitor Supports 4 visitors at the same time Online voitor Supports 4 visitors at the same time Online voitor Supports 4 visitors at the same time Online voitor Supports 4 visitors at the same time Online voitor Supports 4 visitors at the same time Online voitor Supports 4 visitors at the same time Online voitor Supports 4 visitors at the same time Online voitor Supports 5 visitor Supports 5 visit	VEDEN			★3 MP Ultra HD	
# Soft light design, presenting a full color image in 24 hours  # Human detection, real time alerts  # Remote access, view the monitoring areas anytime and anywhere  # Remote access, view the monitoring areas anytime and anywhere  # Remote access, view the monitoring areas anytime and anywhere  # Remote access, view the monitoring areas anytime and anywhere  # Remote access, view the monitoring areas anytime and anywhere  # Remote access, view the monitoring areas anytime and anywhere  # Remote access, view the monitoring areas anytime and anywhere  # Remote access, view the monitoring areas anytime and anywhere  # Remote access, view the monitoring areas anytime and anywhere  # Remote access, view the monitoring areas anytime and anywhere  # Remote access anytime and anywhere  # Remote access anytime and the same time  # Remote access anytime and the same time  # Remote access and the same time  # Remote access anytime and anywhere  # Remote access and a same access an				★ Black light full color, presenting color image even with no supplement light	
# HisP limage processing technology, preserving true colors # Human detection, real time alerts # Remote access, view the monitoring areas anytime and anywhere  Parameters    Parameters				★F1.6 large aperture, clearer night vision	
No.   Sorts   Type				★ Soft light design, presenting a full color image in 24 hours	
Sorts   Type				★ISP image processing technology, preserving true colors	
No.   Sorts   Type				★Human detection, real time alerts	
No.   Sorts   Type				★ Remote access, view the monitoring areas anytime and anywhere	
Collection   Col					
Online visitor   Supports 4 visitors at the same time					
APP O-KAM pro Sigmastar SSC335 Lens 4mm E1.6 Image sensor 1/2.9 CMOS sensor Minimum illumination 0.0.01Lux Sensor performance Support automatic white balance, automatic gain control and automatic backlight compensation Night Vision 6 warm lights, full color night vision Pan&tilt angle Pan 310*, till 50° Video Resolution 2304*1296*(25F8)3 MP Night Vision Compression 1204*1296*(25F8)3 MP Night Vision Compression standard 1.264*1296*(25F8)3 MP Night Vision Compression standard 1.264*(25F8)3 MP Night Vision Compression standard 1.26*(25F8)3 MP Night Vision Compression standard 1.264*(25F8)3 MP Ni		System			
CPU Sigmastar SSC335 Lens Amm F1.6  Response sensor J2.9 CMOS sensor Minimum illumination 0.01Lux Sensor performance Support automatic white balance, automatic gain control and automatic backlight compensation Night Vision Faul Color night vision Panakillt angle Pan 310*, Jill 80° Viewing angle Diagonal: 91* horizontal: 77.3* vertical: 42.9* Resolution J304*1258P(75FS/3 MP Night Vision Full Color night vision Compression standard H.264+/H.264 /MIPEF/JPEG Resolution Romer Full Color night vision Ricurry (Ill color night vision automatically adjusting the brightness of the lights according to the environment Bit rate 128 - 4096kbps mage adjustment Brightness, contrast, OSD display linput Bullt-in 820X speaker Sampling frequency/bit width Compression standard/Bit Rate Output Sullt-in 820X speaker Sampling frequency/bit width Compression standard/Bit Rate Output Bullt-in 820X speaker Sampling frequency/bit width Compression standard/Bit Rate Output Bullt-in 820X speaker Sampling frequency/bit width Compression standard/Bit Rate Output Bullt-in 820X speaker Sampling frequency/bit width Sight Compression standard/Bit Rate Output Bullt-in 820X speaker Sampling frequency/bit width Compression standard/Bit Rate Output Bullt-in 820X speaker Sampling frequency/bit width Compression standard/Bit Rate Output Bullt-in 820X speaker Sampling frequency/bit width Sight-Romerophone Output Bullt-in 820X speaker Samt notification sound triggered Intelligent alarm sound Set different sounds, so that you can know exactly which device is triggered Intelligent alarm sound Set different equipment alarm sounds, so that you can know exactly which device is triggered Intelligent alarm sound Set different equipment alarm sounds, according to different scenarios Network interface 10Mbps/100Mbps adaptive/RAS interface Network protocol 17CP/PHTT-PLT-DID-PHCP_DNS,NTP,RTSP,P2P etc. Wireless require encryption Settlement Frequency Protocol 17CP/PHTT-PLT-DID-PHCP_DNS,NTP,RTSP,P2P etc. Wireless require encryption Settlement Protocol 17CP/PHTT-PLT-D	1				
Lens   Amm F1.6   Image sensor   17.2 9 CMOS sensor			APP	O-KAM pro	
Collection		Collection	CPU	Sigmastar SSC335	
Collection   Minimum illumination   Colltux   Sensor performance   Support automatic white balance, automatic gain control and automatic backlight   compensation   Night Vision   6 warm lights, full color night vision   Pan&tilt angle   Diagonal: 91* horizontal: 77.3* vertical: 42.9*   Viewing angle   Diagonal: 91* horizontal: 77.3* vertical: 42.9*   Resolution   2304*1296P/25FP5/3 MP   Night Vision   Compression standard   C.264*H.726*H.			Lens	4mm F1.6	
Sensor performance   Support automatic white balance, automatic gain control and automatic backlight compensation			Image sensor	1/2.9 CMOS sensor	
Sensor performance Night Vision			Minimum illumination	0.01Lux	
Night Vision   6 warm lights, full color night vision   Pan&tit angle   Pan 310*, tilt 90 ° Viewing angle   Diagonal: 31 ° 13" horizontal: 77.3" vertical: 42.9"	2		Sensor performance	1 ''	
Pan&tilt angle Pan 310 *, riit 90 * Viewing angle Diagonal: 91* hortzontal: 77.3* vertical: 42.9*  Resolution 2304*1296*25FS/3 Mp Night Vision Full color night vision Compression standard H.264* /H.264 /MIPEF/IPEG Rontrol NoRUT, full color night vision, automatically adjusting the brightness of the lights according to the environment Bit rate 128 * 4096kbps Image adjustment Brightness, contrast, 050 display Input Built-in-38dB microphone Output Sampling frequency/bit width Sampling frequency/bit width Compression standard/Bit Rate G731A Humanoid detection Human tracking Human tracking, automatically following after detecting a person Area detection Free daub, only monitoring the areas concerned by users Different devices push different sounds, so that you can know exactly which device is triggered Intelligent alarm sound Set different equipment alarm sounds according to different scenarios  Network interface 10Mbps/100Mbps adaptive/RJ45 interface Network protocol TCP/P.HTTP.TCP,UDP.DHCP,DNS,NTP,RTSP,P2P etc. Wireless requency 2.4-GHz Wireless requency 2.4-GHz Wireless frequency 2.4-GHz Wireless requency 2.4-GHz Wireless requency 3.4-GHz Alarm Alarm detection Motion detection, human framing, human tracking, siren sound, a area detection Pan&Tilt Rotation angle Horizontal 310 "/Vertical 90 * Presets Support 16 presets (mobile app only supports 5) Rated voltage Power consumption Power: 7.4-W (warm light on), maximum power: 12.8-W Power consumption Power: 7.4-W (warm light on), maximum power: 12.8-W Power consumption Power: 7.4-W (warm light on), maximum power: 12.8-W Power consumption Power: 7.4-W (warm light on), maximum power: 12.8-W Power consumption Power: 7.4-W (warm light on), maximum power: 12.8-W			Night Vision	•	
Viewing angle   Diagonal: 91* horizontal: 77.3* vertical: 42.9*			Pan&tilt angle		
Resolution   2304*1296P/25FPS/3 MP   Night Vision   Full color night vision   Compression standard   H.264+ /H.264+					
Night Vision   Full color night vision   Full color night vision   H.264+/H.264 /MIPEF/IPEG     IR control   No IRCUT, full color night vision, automatically adjusting the brightness of the lights according to the environment					
Video   Rontrol   Rontrol   No IRCUT, full color night vision, automatically adjusting the brightness of the lights according to the environment		Video			
Recontrol   No IRCUT, full color night vision, automatically adjusting the brightness of the lights according to the environment	3				
Recontrol   according to the environment			Compression standard		
Bit rate   128 ~ 4096kbps     Image adjustment   Brightness, contrast, OSD display     Input   Built-in-38dB microphone     Output   Sekher   Output   Output     Output   Output   Output     Output   Output   Output   Output     Output   Output   Output   Output     Output   Output   Output   Output     Output   Output   Output   Output     Output   Output   Output   Output     Output   Output   Output   Output     Output   Output   Output   Output   Output     Output   Output   Output   Output     Output   Output   Output   Output     Output   Output   Output   Output     Output   Output   Output   Output     Output   Output   Output   Output     Output   Output   Output   Output     Output   Output   Output   Output     Output   Output   Output   Output     Output   Output   Output   Output     Output   Output   Ou			IR control		
Input   Built-in-38dB microphone			Bit rate		
Audio   Aud			Image adjustment	Brightness, contrast, OSD display	
Audio  Output Sampling frequency/bit width Compression standard/Bit Rate  Humanoid detection Human tracking Humanoid detection, filtering invalid video events Human tracking Human tracking, automatically following after detecting a person Area detection Free daub, only monitoring the areas concerned by users  Different devices push different sounds, so that you can know exactly which device is triggered Intelligent alarm sound Set different equipment alarm sounds according to different scenarios  Network interface Network protocol TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc. Wireless network Wireless frequency Wireless frequency Wireless security encryption 64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption  External TF card Support TF card (up to 256GB) Cloud storage Support cloud storage Motion detection, human detection, human framing, human tracking, siren sound, a area detection Presets Supports 16 presets (mobile app only supports 5)  Rated voltage Power consumption Power: 7.4W (warm light on), maximum power: 12.8W Power consumption Power: 7.4W (warm light on), maximum power: 12.8W Weight (Note: in kind prevail)		Audio		Built-in-38dB microphone	
Audio Sampling frequency/bit width Compression standard/Bit Rate  Humanoid detection Human tracking Humanoid detection, filtering invalid video events Human tracking Human tracking, automatically following after detecting a person Area detection Free daub, only monitoring the areas concerned by users Smart notification sound Different devices push different sounds, so that you can know exactly which device is triggered Intelligent alarm sound Set different equipment alarm sounds according to different scenarios  Network interface Network protocol TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc. Wireless network Wireless frequency Wireless frequency Wireless security encryption  54/128-bit WEP/WPA-PSK/WPA2-PSK data encryption  External TF card Support TF card (up to 256GB) Cloud storage Support cloud storage Motion detection, human detection, human framing, human tracking, siren sound, a area detection Presets Supports 16 presets (mobile app only supports 5)  Rated voltage Power consumption Power: 7.4W (warm light on), maximum power: 12.8W Physical Indicators Weight (Note: in kind prevail)				Built-in 802W speaker	
Compression standard/Bit Rate Compression standard/Bit Rate Al  Humanoid detection Human tracking Human tracking, automatically following after detecting a person Free daub, only monitoring the areas concerned by users Smart notification sound Intelligent alarm sound Set different equipment alarm sounds according to different scenarios  Network interface Network protocol TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc. Wireless network Wireless network Wireless frequency Wireless security encryption Storage Alarm Alarm detection  Alarm detection  Pan&Tilt  Physical Indicators  Physical Indicators  Physical Indicators  Area detection Humanoid detection, filtering invalid video events Humanotracking, automatically following after detecting a person Human tracking, automatically following after detecting a person Free daub, only monitoring the areas concerned by users  Free daub, only monitoring the areas concerned by users  Free daub, only monitoring the areas concerned by users  Free daub, only monitoring the areas concerned by users  Free daub, only monitoring the areas concerned by users  Free daub, only monitoring the areas concerned by users  Free daub, only monitoring the areas concerned by users  Free daub, only monitoring the areas concerned by users  Free daub, only monitoring the areas concerned by users  Free daub, only monitoring the areas concerned by users  Free daub, only monitoring the areas concerned by users  Free daub, only monitoring the areas concerned by users  Free daub, only monitoring the areas concerned by users  Free daub, only monitoring the areas concerned by users  Free daub, only monitoring the areas concerned by users  Free daub, only monitoring the areas concerned	4				
AI  AI  Humanoid detection Humanoid detection, filtering invalid video events  Human tracking Human tracking, automatically following after detecting a person  Free daub, only monitoring the areas concerned by users  Different devices push different sounds, so that you can know exactly which device is triggered  Intelligent alarm sound Set different equipment alarm sounds according to different scenarios  Network interface 10Mbps/100Mbps adaptive/RJ45 interface  Network protocol TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc.  Wireless network IEEE802.11b/g/n  Wireless security encryption 64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption  External TF card Support TF card (up to 256GB)  Cloud storage Support cloud storage  Alarm Alarm detection Motion detection, human framing, human tracking, siren sound, a area detection  Persets Supports 16 presets (mobile app only supports 5)  Rated voltage DC12V±5%  Power consumption Power: 7.4W (warm light on), maximum power: 12.8W  Power consumption Temperature: -10 ~ 50°C; Humidity: < 90%  Weight (Note: in kind prevail)					
Al Human tracking Human tracking, automatically following after detecting a person  Area detection Free daub, only monitoring the areas concerned by users  Different devices push different sounds, so that you can know exactly which device is triggered  Intelligent alarm sound Set different equipment alarm sounds according to different scenarios  Network interface 10Mbps/100Mbps adaptive/RJ45 interface Network protocol TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc.  Wireless network IEEE802.11b/g/n Wireless requency 2.4GHz Wireless security encryption 64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption  External TF card Support TF card (up to 256GB)  Cloud storage Support cloud storage  8 Alarm Alarm detection Motion detection, human detection, human framing, human tracking, siren sound, a area detection  Motion detection, human detection, human framing, human tracking, siren sound, a area detection  Presets Supports 16 presets (mobile app only supports 5)  Rated voltage DC12V±5%  Power consumption Power: 7.4W (warm light on), maximum power: 12.8W  Operating condition Temperature: -10 ~ 50°C; Humidity: < 90% Weight (Note: in kind prevail)		Al	<u>'</u>		
Area detection Free daub, only monitoring the areas concerned by users    Smart notification sound   Different devices push different sounds, so that you can know exactly which device is triggered	5				
Smart notification sound   Different devices push different sounds, so that you can know exactly which device is triggered					
Smart notification sound   triggered			Area detection		
Network   Netw			Smart notification sound		
Network  Net			Intelligent alarm sound	Set different equipment alarm sounds according to different scenarios	
Network   Netw	6	Network	Network interface	10Mbps/100Mbps adaptive/RJ45 interface	
Network   Wireless network   Wireless frequency   2.4GHz					
Wireless frequency Wireless security encryption  7 Storage  8 Alarm Alarm detection  Rotation angle Presets  Rated voltage  Power consumption  Physical Indicators  Wireless frequency Wireless frequency Wireless security encryption 64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption Support TF card (up to 256GB)  Support cloud storage  Motion detection, human framing, human tracking, siren sound, a area detection Horizontal 310 °/Vertical 90 °  Supports 16 presets (mobile app only supports 5)  Rated voltage Power consumption Power: 7.4W (warm light on), maximum power: 12.8W  Operating condition Temperature: -10 ~ 50°C; Humidity: < 90% Weight (Note: in kind prevail)					
Wireless security encryption 64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption  Storage  External TF card Support TF card (up to 256GB)  Support cloud storage  Motion detection, human detection, human framing, human tracking, siren sound, a area detection  Rotation angle Horizontal 310 °/Vertical 90 °  Presets Supports 16 presets (mobile app only supports 5)  Rated voltage DC12V±5%  Power consumption Power: 7.4W (warm light on), maximum power: 12.8W  Operating condition Temperature: -10 ~ 50°C; Humidity: < 90%  Weight (Note: in kind prevail)					
The storage and the storage and the storage and the storage and the storage are storage.  8			. ,		
7 Storage Cloud storage Support cloud storage  Motion detection, human detection, human framing, human tracking, siren sound, a area detection  Pan&Tilt  Rotation angle Horizontal 310 °/Vertical 90 ° Presets Supports 16 presets (mobile app only supports 5)  Rated voltage DC12V±5% Power consumption Power: 7.4W (warm light on), maximum power: 12.8W  Operating condition Temperature: -10 ~ 50°C; Humidity: < 90% Weight (Note: in kind prevail)			1 11		
8 Alarm Alarm detection Motion detection, human detection, human framing, human tracking, siren sound, a area detection  9 Pan&Tilt  Rotation angle Horizontal 310 °/Vertical 90 °  Presets Supports 16 presets (mobile app only supports 5)  Rated voltage DC12V±5%  Power consumption Power: 7.4W (warm light on), maximum power: 12.8W  Operating condition Temperature: -10 ~ 50°C; Humidity: < 90%  Weight (Note: in kind prevail)		_			
Presets  Rotation angle  Presets  Rotation angle  Presets  Supports 16 presets (mobile app only supports 5)  Rated voltage  Power consumption  Power: 7.4W (warm light on), maximum power: 12.8W  Operating condition  Temperature: -10 ~ 50°C; Humidity: < 90%  Weight  (Note: in kind prevail)				- 11	
Presets Supports 16 presets (mobile app only supports 5)  Rated voltage Power consumption Power: 7.4W (warm light on), maximum power: 12.8W  Operating condition Temperature: -10 ~ 50°C; Humidity: < 90% Weight (Note: in kind prevail)	8	Alarm		area detection	
Presets Supports 16 presets (mobile app only supports 5)  Rated voltage DC12V±5%  Power consumption Power: 7.4W (warm light on), maximum power: 12.8W  Operating condition Temperature: -10 ~ 50°C; Humidity: < 90%  Weight (Note: in kind prevail)	9	Pan&Tilt	Rotation angle	Horizontal 310 */Vertical 90 *	
Power consumption Power: 7.4W (warm light on), maximum power: 12.8W  Operating condition Temperature: -10 ~ 50°C; Humidity: < 90%  Weight (Note: in kind prevail)			Presets	Supports 16 presets (mobile app only supports 5)	
Physical Indicators Operating condition Temperature: -10 ~ 50°C; Humidity: < 90% Weight (Note: in kind prevail)	10	Physical Indicators	Rated voltage	DC12V±5%	
Weight (Note: in kind prevail)			Power consumption	Power: 7.4W (warm light on), maximum power: 12.8W	
Weight (Note: in kind prevail)			Operating condition	Temperature: -10 ~ 50°C; Humidity: < 90%	
		1		<u> </u>	