CS64			
Product Image			Features
			★Pan&tilt, two way audio
			★ Black and white night vision, full color night vision optional
			★ ISP image processing technology, preserving true colors
		(f)	Human detection, real time alerts
No	Conto	Turne	
No.	Sorts	Type	Parameters Linux
1	System	Operating system Online visitor	Supports 4 visitors at the same time
		APP	O-KAM Pro
		CPU	Ingenic T23
	Collection		512Mb
2		Memory	4mm F2.0
		Lens	
		Image sensor	1/2.7" 1080p progressive scan CMOS sensor
		Minimum illumination	0.5Lux (color mode), 0.1Lux (b&w mode)
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight compensation
		Night vision	Black and white night vision, full-color night vision
		Viewing angle	91°
	Video	Resolution	1920x1080/15FPS/2MP, 1080P; 2304x1296/15FPS/3MP, 1296P
		Night vision	Black and white night vision, full-color night vision
3		Compression standard	H.264 main profile/Motion-JPEG/JPEG
		IR control	IR-CUT, soft photosensitive control
		Bit rate	128 ~ 4096kbps
		Image adjustment	Brightness, contrast, OSD display
	Audio	Input	Built-in -38dB microphone
4		Output	Built-in 8Ω1W speaker
		Sampling frequency/bit width	8KHz/16bit
		Compression standard/Bit Rate	G711A
5	Pan/Tilt	Rotation angle	Pan: 265° tilt: 95°
	Network	Network interface	10Mbps/100Mbps
		Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P
6		Wireless network	IEEE802.11b/g/n
		Wireless frequency	2.4G
		Wireless security encryption	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
7	Storage	External TF card	Supports T-Flash cards (up to 256GB)
		Cloud storage	Support cloud storage, users can purchase according to their needs.
8	Alarm	Alarm detection	Motion detection, human detection, human framing,human tracking , siren alarm and area detection
9	Physical Indicators	Rated voltage	DC12V±5%
		Power consumption	Power: 4.32W (0.37A) Maximum power: 9.36W (0.78A)
		Operating condition	Working temperature: -10~55 $^\circ$ C, working humidity<90%
		Weight	Net weight: 460g; Gross weight: 840g
		Camera size	171x112x179mm
		Packaging box size	195x205x130mm
		Carton size	545x425x415mm,16PCS/CARTON