| CS663DR | | | |
|---------------|---------------------|--|---|
| Product Image | | duct Image | Features |
| | | | ★ Dual lens dual view leaves no blind spots |
| | | | ★F2.0 large aperture, more light intake, clearer night vision |
| | | | ★ISP image processing technology, preserving true colors |
| | | | |
| | | | ★ Human detection, real time alerts |
| No. | Sorts | Туре | Parameters |
| | System | Operating system | Linux |
| 1 | | Online visitor | Supports 4 visitors at the same time |
| | | APP | O-KAM Pro |
| | Collection | CPU | Ingenic |
| | | Memory | 512Mb |
| | | Lens | 4mm |
| 2 | | Image sensor | 1/2.7" 1080p progressive scan CMOS sensor |
| _ | | Min. Illumination | 0.5Lux (color mode), 0.1Lux (b&w mode) |
| | | Sensor performance | Support automatic white balance, automatic gain control and automatic backlight compens |
| | | Night vision | Black and white night vision, full-color night vision |
| | | Viewing angle | 91° |
| | Video | Resolution | 1080P 1920x1080/15FPS/2MP; 1296P 2304x1296/15FPS/3MP |
| | | Night vision | Black and white night vision, full-color night vision |
| 2 | | Compression standard | H.264 main profile/Motion-JPEG/JPEG |
| 3 | | IR control | IR-CUT, soft photosensitive control |
| | | Bit rate | 128 ~ 4096kbps |
| | | Image adjustment | Brightness, contrast, OSD display |
| | Audio | Input | Built-in-38dB microphone |
| | | Output | Built-in 8Ω1W speaker |
| 4 | | Sampling frequency/bit width | 8KHz/16bit |
| | | Compression standard/Bit Rate | G711A |
| 5 | Pan/Tilt | Rotation angle | Horizontal: 350° Vertical: 90° |
| | Network | Network interface | 10Mbps/100Mbps adaptive/RJ45 interface |
| | | Network protocol | TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P |
| 6 | | Wireless network | IEEE802.11b/g/n |
| , | | Wireless frequency | 2.4G |
| | | Wireless requercy Wireless security encryption | 64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption |
| | | External TF card | Supports T-Flash cards (up to 256GB) |
| 7 | Storage | Cloud storage | Support cloud storage, users can purchase according to their needs. |
| 8 | | Alarm detection | Motion detection, human detection, human framing, siren alarm and area detection |
| 0 | Physical Indicators | Rated voltage | DC12V±5% |
| | | _ | Power: 6.24W (0.52A) Maximum power: 10.92W (0.91A) |
| | | Power consumption | |
| 9 | | Operating condition | Working temperature: -10~55 °C, working humidity<90% |
| | | | Net weight: 545g . Gross weight: 845g |
| | | Camera size | 183x141x237mm |
| | | Packaging box size | 253x200x153mm |