

E3T-5LRV(3.6)

5MP Dual Light Dome Camera
with MIC



☰ Features

- 1/3" CMOS Sensor
- Support H.264/H.265
- Support ONVIF Profiles
- Ingress Protection: IP66
- 3 White Lights and 3 IR Lights
- Support DWDR, 3D Noise Reduction, Backlight Compensation, and White Balance, Suitable for Different Monitoring Environments
- Support Audio Input, Audio and Video Synchronization
- Support Mobile App Remote Monitoring
- Build-in MIC

Model E3T-5LRV(3.6)
Major Specifications

| | | |
|-------------------------------|-----------------------------------|--|
| Camera | Image Sensor | 1/ 3" CMOS |
| | Maximum Resolution | 2880 (H)*1624 (V) |
| | Effective Pixels | 5.0MP |
| | Video Compression Standard | H.265/H.264 |
| | Frame Rate | Main stream:5MP(2880*1624)@20fps/ 4MP(2560*1440)@25fps Subcode stream:448P(800*448)/D1(704*576)/360P(640*360) / CIF(352*288 |
| | Code Stream | Dual Stream |
| | Video Steam | Support VBR,CBR |
| | Focal Length | 3.6mm |
| | Max Aperture | F2.0 |
| | Lens Aperture Type | Fixed iris |
| | Angle of View | H 76° , V 40° , D: 93.4° |
| | White Light Range | 20m |
| | White Light | 3 |
| | IR Range | 30m |
| | Infrared light | 3 |
| Minimum illumination | 0.02lux | |
| Function | Motion Detection | Support |
| | Email Alert | Not Support |
| | Image Rotation | Support |
| | Wide Dynamic | Support DWDR |
| | SD card | Not Support |
| | External Audio Input | Not Support |
| | Ethernet | 10M/100M Ethernet, RJ45 port |
| Network | Protocol | ONVIF, P2P, CGI, HTTP, TCP/IP, IPv4, RTSP, UDP, NTP, DHCP, DNS |
| | Client | HOLOZ VMS, HOLOZ App |
| | WEB Interface | Support English/Chinese/Russian/Japanese/Korean/Italiano/Português |
| Intelligent | Intrusion Detection | Support |
| | Crossing Detection | Support |
| | Off-duty Detection | Support |
| | Passenger Flow Statistics | Support |
| General Specifications | | |
| Power type | 12V DC 1 A and PoE (IEEE 802.3af) | |
| Power consumption | Day ≤3W Night ≤7W | |
| Operating temperature | -30°C to +60°C | |
| Operating humidity | 10% to 90% (Non-Condensing) | |
| IP rating | IP66 | |
| Weight | 290g | |
| Dimension | 101.7mm*101.7mm*102.4mm (L*W*H) | |
| Dimension (With Package) | 115mm*115mm*110mm (L*W*H) | |

Dimensions

